



# BZX97 ...


## SILICON PLANAR ZENER DIODES

### Features

#### Silicon Planar Zener Diodes

The Zener voltages are graded according to the international E 24 standard. Other voltage tolerances on request.

#### DO-35



DIM	DIMENSIONS				Note
	inches		mm		
	Min.	Max.	Min.	Max.	
A	-	0.154	-	3.9	
B	-	0.075	-	1.9	φ
C	-	0.020	-	0.52	φ
D	1.083	-	27.50	-	

### Absolute Maximum Ratings ( $T_a=25^\circ\text{C}$ )

	Symbols	Values	Units
Zener current see Table "Characteristics"			
Power dissipation at $T_{amb}=25^\circ\text{C}$	$P_{tot}$	500 <sup>(1)</sup>	mW
Junction temperature	$T_j$	175	$^\circ\text{C}$
Storage temperature range	$T_s$	-55 to +175	$^\circ\text{C}$

Note:

(1) Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case.

### Characteristics at $T_{amb}=25^\circ\text{C}$

	Symbols	Min.	Typ.	Max.	Units
Thermal resistance junction to ambient Air	$R_{thA}$	-	-	0.3 <sup>(1)</sup>	K/mW
Forward voltage at $I_F=100\text{mA}$	$V_F$	-	-	1.0	V

Note:

(1) Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case.

Type	Zener voltage range <sup>1)</sup>			Dynamic resistance			Reverse leakage current			Temp. coefficient of Zener voltage
	V <sub>znom</sub>	I <sub>zT</sub> for V <sub>zT</sub> <sup>3)</sup>		r <sub>zT</sub> and r <sub>zK</sub> at I <sub>zK</sub>			I <sub>R</sub> and I <sub>R</sub> <sup>3)</sup> at V <sub>R</sub>			TK <sub>VZ</sub>
	V	mA	V	Ω	Ω	mA	nA	uA	V	%/K
BZX97/C 2V4	2.4	5	2.28 ... 2.56	<85	<600	1	<10000	<50	1	135
BZX97/C 2V7	2.7	5	2.5 ... 2.9	<85	<600	1	<10000	<50	1	135
BZX97/C 3V0	3.0	5	2.8 ... 3.2	<85	<600	1	<4000	<40	1	125
BZX97/C 3V3	3.3	5	3.1 ... 3.5	<85	<600	1	<2000	<40	1	115
BZX97/C 3V6	3.6	5	3.4 ... 3.8	<85	<600	1	<2000	<40	1	105
BZX97/C 3V9	3.9	5	3.7 ... 4.1	<85	<600	1	<2000	<40	1	95
BZX97/C 4V3	4.3	5	4.0 ... 4.6	<75	<600	1	<1000	<20	1	90
BZX97/C 4V7	4.7	5	4.4 ... 5.0	<60	<600	1	<500	<10	1	85
BZX97/C 5V1	5.1	5	4.8 ... 5.4	<35	<550	1	<100	<2	1	80
BZX97/C 5V6	5.6	5	5.2 ... 6.0	<25	<450	1	<100	<2	1	70
BZX97/C 6V2	6.2	5	5.8 ... 6.6	<10	<200	1	<100	<2	2	64
BZX97/C 6V8	6.8	5	6.4 ... 7.2	<8	<150	1	<100	<2	3	58
BZX97/C 7V5	7.5	5	7.0 ... 7.9	<7	<50	1	<100	<2	5	53
BZX97/C 8V2	8.2	5	7.7 ... 8.7	<7	<50	1	<100	<2	6	47
BZX97/C 9V1	9.1	5	8.5 ... 9.6	<10	<50	1	<100	<2	7	43
BZX97/C 10	10	5	9.4 ... 10.6	<15	<70	1	<100	<2	7.5	40
BZX97/C 11	11	5	10.4 ... 11.6	<20	<70	1	<100	<2	8.5	36
BZX97/C 12	12	5	11.4 ... 12.7	<20	<90	1	<100	<2	9	32
BZX97/C 13	13	5	12.4 ... 14.1	<26	<110	1	<100	<2	10	29
BZX97/C 15	15	5	13.8 ... 15.6	<30	<110	1	<100	<2	11	27
BZX97/C 16	16	5	15.3 ... 17.1	<40	<170	1	<100	<2	12	24
BZX97/C 18	18	5	16.8 ... 19.1	<50	<170	1	<100	<2	14	21
BZX97/C 20	20	5	18.8 ... 21.2	<55	<220	1	<100	<2	15	20
BZX97/C 22	22	5	20.8 ... 23.3	<55	<220	1	<100	<2	17	18
BZX97/C 24	24	5	22.8 ... 25.6	<80	<220	1	<100	<2	18	16
BZX97/C 27	27	5	25.1 ... 28.9	<80	<220	1	<100	<2	20	14
BZX97/C 30	30	5	28 ... 32	<80	<220	1	<100	<2	22	13
BZX97/C 33	33	5	31 ... 35	<80	<220	1	<100	<2	24	12
BZX97/C 36	36	5	34 ... 38	<90	<250	1	<100	<2	26	11
BZX97/C 39	39	2.5	37 ... 41	<100	<600 <sup>2)</sup>	0.5	<100	<2	28	10
BZX97/C 43	43	2.5	40 ... 46	<100	<700 <sup>2)</sup>	0.5	<100	<2	32	9.2
BZX97/C 47	47	2.5	44 ... 50	<120	<1000 <sup>2)</sup>	0.5	<100	<2	34	8.5
BZX97/C 51	51	2.5	48 ... 54	<135	<1000 <sup>2)</sup>	0.5	<100	<2	36	7.8

Notes:

(1) Tested with pulses tp=20ms.

(2) Measured at I<sub>z</sub>=0.5mA

(3) Valid provided that leads are kept at ambient temperature at a distance of 8 mm from case.