



Features

- Lead free as standard
- RoHS compliant*
- Low forward voltage
- Extremely thin/leadless package
- Majority carrier conduction
- Designed for mounting on small surface

Applications

- Cellular phones
- PDAs
- Notebooks
- GPS

CD1005-B0520 – Surface Mount Schottky Barrier Diode

General Information

The markets of portable communications, computing and video equipment are challenging the semiconductor industry to develop increasingly smaller electronic components. Bourns offers Schottky Barrier Diodes for these applications, in compact chip package 1005 (SOD323) size format, which offer PCB real estate savings and are considerably smaller than most competitive parts. The Schottky Barrier Diodes offer a forward current of 0.5 A with a repetitive peak reverse voltage of 30 V.

Bourns® Chip Diodes conform to JEDEC standards, are easy to handle on standard pick and place equipment and their flat configuration minimizes roll away.

Electrical Characteristics (@ T_A = 25 °C Unless Otherwise Noted)

Parameter	Symbol	Min.	Nom.	Max.	Unit
Repetitive Peak Reverse Voltage	V _{RRM}			30	V
Reverse Voltage	V _R			20	V
Average Forward Rectified Current	I _O			0.5	A
Maximum Instantaneous Forward Voltage @ I _F = 1.0 A	V _F		0.45	0.55	V
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}			2	A
Forward Voltage (I _F = 100 mA)	V _F		0.25	0.36	V
Forward Voltage (I _F = 500 mA)	V _F		0.35	0.47	V
Reverse Current (V _R = 20 V)	I _R			100	μA
Capacitance between terminals (f = 1 MHz, and 0 VDC reverse voltage)	C _T		100		pF

Thermal Characteristics (@ T_A = 25 °C Unless Otherwise Noted)



Parameter	Symbol	CD1005-B0520	Unit
Junction Temperature Range	T _J	-40 to +125	°C
Storage Temperature Range	T _{STG}	-40 to +125	°C

CD1005-B0520 – Surface Mount Schottky Barrier Diode




Product Dimensions

This is a lead free product. It is a SOD-323F (1005) standard package, molded plastic. The terminals are Gold plated and are solderable per MIL-STD-750, Method 2026. The polarity is indicated by a cathode band. The package weighs approximately 0.006 g. The package and dimensions are shown below



Dimensions	
A	$\frac{2.40 - 2.60}{(0.095 - 0.102)}$
B	$\frac{1.10 - 1.30}{(0.043 - 0.051)}$
C	$\frac{0.70 - 0.90}{(0.027 - 0.035)}$
D	$\frac{0.55}{(0.021)}$ Typ.
E	$\frac{0.30}{(0.012)}$ Typ.
F	$\frac{1.0}{(0.39)}$ Typ.

Recommended Pad Layout



Dimension	1005
A (Max.)	$\frac{2.10}{(0.082)}$
B (Min.)	$\frac{1.20}{(0.047)}$
C (Min.)	$\frac{1.20}{(0.047)}$

DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

How To Order

CD 1005 - B 05 20

Common Code _____
 Chip Diode

Package _____
 • 1005

Model _____
 B = Schottky Barrier Series

Average Forward Current (I_F) Code _____
 05 = 500 mA
 (Code x 1000 mA = Average Forward Current)

Reverse Voltage (V_R) Code _____
 20 = 20 V


*RoHS Directive 2002/95/EC Jan 27 2003 including Annex
 Specifications are subject to change without notice.
 Customers should verify actual device performance in their specific applications.

CD1005-B0520 – Surface Mount Schottky Barrier Diode


BOURNS®

Rating and Characteristic Curves


Typical Capacitance




Current Derating Curve



Forward Characteristics



Reverse Characteristics




CD1005-B0520 – Surface Mount Schottky Barrier Diode

BOURNS®

Packaging Information

The surface mount product is packaged in an 8 mm x 4 mm tape and reel format per EIA-481 standard.



Item	Symbol	1005 (SOD323)
Carrier Width	A	$\frac{1.90 \pm 0.10}{(0.075 - 0.004)}$
Carrier Length	B	$\frac{4.30 \pm 0.10}{(0.169 - 0.004)}$
Carrier Depth	C	$\frac{1.80 \pm 0.10}{(0.071 - 0.004)}$
Sprocket Hole	d	$\frac{1.55 \pm 0.05}{(0.061 - 0.002)}$
Reel Outside Diameter	D	$\frac{178}{(7.008)}$
Reel Inner Diameter	D ₁	$\frac{80.0}{(3.150)}$ Min.
Feed Hole Diameter	D ₂	$\frac{13.0 \pm 0.20}{(0.512 - 0.008)}$
Sprocket Hole Position	E	$\frac{1.75 \pm 0.10}{(0.069 - 0.004)}$
Punch Hole Position	F	$\frac{3.50 \pm 0.05}{(0.138 - 0.002)}$
Punch Hole Pitch	P	$\frac{4.00 \pm 0.10}{(0.157 - 0.004)}$
Sprocket Hole Pitch	P ₀	$\frac{4.00 \pm 0.10}{(0.157 - 0.004)}$
Embossment Center	P ₁	$\frac{2.00 \pm 0.05}{(0.079 - 0.002)}$
Overall Tape Thickness	T	$\frac{0.20 \pm 0.10}{(0.008 - 0.004)}$
Tape Width	W	$\frac{8.00 \pm 0.20}{(0.315 - 0.008)}$
Reel Width	W ₁	$\frac{13.5}{(0.531)}$ Max.
Quantity per Reel	—	2,500



Reliable Electronic Solutions

Asia-Pacific:

Tel: +886-2 2562-4117 • Fax: +886-2 2562-4116

Europe:

Tel: +41-41 768 5555 • Fax: +41-41 768 5510

The Americas:

Tel: +1-951 781-5500 • Fax: +1-951 781-5700

www.bourns.com

*RoHS Directive 2002/95/EC Jan 27 2003 including Annex Specifications are subject to change without notice. Customers should verify actual device performance in their specific applications.