

# ISOCOM<sup>®</sup>



Hutton Close, Crowther Ind Est, Washington, Tyne & Wear NE38 0AH, England  
[Email: enquiry@isocomoptocouplers.com](mailto:enquiry@isocomoptocouplers.com) - Tel: +44 (0)191 4166546 - Fax: +44 (0)191 4155055

## CNG35, CNG36, CNG39 CNX35, CNX36, CNX39 OPTICALLY COUPLED ISOLATORS

[Circuit](#)

[Features](#)

[Description](#)

[Absolute Maximum Ratings](#)

[Electro-optical Characteristics](#)


[Similar Optocouplers](#)

[Home Page](#)



---

### Circuit



### Features

- 3120-4400 Volt Isolation.
- High DC Current Transfer Ratio.
- Low Cost Dual-In-Line Package.
- Working Voltage 2500 VDC

### Description

The CNG/CNX Series are optically coupled isolators consisting of a Gallium Arsenide infrared emitting diode and an NPN silicon phototransistor mounted in a standard 6-pin dual-in-line package. Surface Mount Option Available.

All electrical parameters are 100% tested by manufacturing. Specifications are guaranteed to a cumulative 0.65% AQL

## Absolute Maximum Ratings (Ta=25°C)

Storage Temperature:	-55°C to +150°C
Operating Temperature:	-55°C to +100°C
Lead Soldering:	260°C for 10s, 1.6mm from case
Input-To-Output Isolation Voltage:	3120-4400Vdc

## Input Diode

Forward DC Current:	100mA
Reverse DC Voltage:	5V
Peak Forward Current (1µs p.w. 300pps):	3A
Power Dissipation:	200mW
Derate Linearly:	1.33mW/°C above 25°C

## Output Transistor

Collector-Emitter Voltage:	30V
Power Dissipation:	200mW

## Optocoupler

Collector Cut-off Current (Dark) $I_{CEW}$ :	200nA Max (Vcc=10V; work. volt.=2.5kV Diode; If=0)
Isolation Voltage DC $V_{IO}$ :	4.4kVMin
Isolation Voltage AC (RMS) $V_{IO}$ :	3.12kVMin

## Package

Total Power Dissipation:	250mW
Derate Linearly:	3.3mW/°C above 25°C

## Electro-optical Characteristics (Ta=25°C)

INPUT	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$V_F$	Forward Voltage	$I_F=10mA$			1.5	V
$I_R$	Reverse Current	$V_R=5V$			10	µA
OUTPUT	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$I_{CEO}$	Collector cut-off current (dark)	$V_{CE}=10V$			50	nA
		$V_{CE}=10V, T_A=70°C$			10	µA
		$V_{CB}=10V$			20	nA
	Collector-Emitter Breakdown	$V_{(BR) CEO}$	30			V

	Voltage					
<b>COUPLED</b>	<b>PARAMETER</b>	<b>CONDITIONS</b>	<b>MIN</b>	<b>TYP</b>	<b>MAX</b>	<b>UNIT</b>
$I_C/I_F$	DC Current Transfer Ratio					
	CNG/CNX35	$I_F=10\text{mA}, V_{CE}=5\text{V}$	40		80	%
	CNG/CNX36		63		125	%
	CNG/CNX39		100		200	%
$R_{IO}$	Input-to-Output Isolation Resistance	$V_{IO}=500\text{V}$ , (note 1)	100			Gohm
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage	$I_F=10\text{mA}$ , $I_C=2.5\text{mA}$		0.2	0.4	V
$C_{IO}$	Capacitance Input to Output	$f=1\text{MHz}$ (note 1)		0.6		pf
$T_R$	Output Rise Time	$I_F=10\text{mA}$ , $V_{CC}=5.0\text{V}$		2	4	$\mu\text{s}$
$T_{ON}$	Output Turn-on Time	$R_L=75\text{ohm}$ , $T_A=25^\circ\text{C}$		3	5.6	$\mu\text{s}$
$T_F$	Output Fall Time			2	3.5	$\mu\text{s}$
$T_{OFF}$	Output Turn-off Time			2.5	4.1	$\mu\text{s}$

Isocom takes great effort to ensure accurate data, but regrettably cannot be held liable for any error on its website. Visit [File Lists](#) to confirm old printouts are up-to-date.