




Resistor/Capacitor Networks

ECL Terminators and Line Terminator, Conformal Coated, SIP



FEATURES

- 4 to 18 pins available
- X7R and COG capacitors available
- Low cross talk
- Custom design capability
- "B" 0.250" [6.35 mm], "C" 0.350" [8.89 mm] and "E" 0.325" [8.26 mm] maximum seated height available, dependent on schematic
- 10K ECL terminators, Circuits E and M. 100K ECL terminators, Circuit A. Line terminator, Circuit T



STANDARD ELECTRICAL SPECIFICATIONS									
VISHAY DALE MODEL	PROFILE	SCHEMATIC	RESISTOR CHARACTERISTICS					CAPACITOR CHARACTERISTICS	
			POWER RATING P _{70°C} W	RESISTANCE RANGE Ω	RESISTANCE TOLERANCE ± %	TEMP. COEFF. ± ppm/°C	T.C.R. TRACKING ± ppm/°C	CAPACITANCE RANGE	CAPACITANCE TOLERANCE ± %
CS206	B	E M	0.125	10 - 1M	2, 5	200	100	0.01 μF	10 (K), 20 (M)
CS206	C	T	0.125	10 - 1M	2, 5	200	100	33 pF to 0.1 μF	10 (K), 20 (M)
CS206	E	A	0.125	10 - 1M	2, 5	200	100	0.01 μF	10 (K), 20 (M)


TECHNICAL SPECIFICATIONS		
PARAMETER	UNIT	CS206
Operating Voltage (at + 25 °C)	VAC	50 maximum
Dissipation Factor (maximum)	%	COG = 0.15; X7R = 2.5
Insulation Resistance (at + 25 °C/rated voltage)	MΩ	100 000
Dielectric Test	V	2.5 x rated voltage
Operating Temperature Range	°C	- 55 to + 125 °C

Capacitor Temperature Coefficient:
COG maximum 0.15 %, X7R maximum 2.5 %

Package Power Rating (maximum at 70 °C):
8 PINS = 0.80 W
9 PINS = 0.90 W
10 PINS = 1.00 W

EIA Characteristics:
COG and X7R (COG capacitors may be substituted for X7R capacitors)

SCHEMATICS in inches [millimeters]




GLOBAL PART NUMBER INFORMATION																	
New Global Part Numbering: 20608EC103G471KP (preferred part numbering format)																	
2	0	6	0	8	E	C	1	0	3	G	4	7	1	K	P		
GLOBAL MODEL	PIN COUNT	PACKAGE/SCHEMATIC	CHARACTERISTIC	RESISTANCE VALUE	RES. TOLERANCE	CAPACITANCE VALUE	CAP. TOLERANCE	PACKAGING	SPECIAL								
206 = CS206	04 = 4 Pin 08 = 8 Pin 18 = 18 Pin	E = BE M = BM A = EA T = CT S = Special	C = COG X = X7R S = Special	2 digit significant figure, followed by a multiplier 100 = 10 Ω 333 = 33 kΩ 105 = 1 MΩ	G = ± 2 % J = ± 5 % S = Special	(in pF) 2 digit significant figure, followed by a multiplier 330 = 33 pF 392 = 3900 pF 104 = 0.1 μF	K = ± 10 % M = ± 20 % S = Special	E = Lead (Pb)-free, Bulk P = Tin/Lead, Bulk	Blank = Standard (Dash Number) (up to 2 digits)								
Historical Part Number example: CS20608BEC103G471KP03 (will continue to be accepted)																	
CS206	08	B	E	C	103	G	471	K	P03								
HISTORICAL MODEL	PIN COUNT	PACKAGE HEIGHT	SCHEMATIC	CHARACTERISTIC	RESISTANCE VALUE	RESISTANCE TOLERANCE	CAPACITANCE VALUE	CAPACITANCE TOLERANCE	PACKAGING								




Resistor/Capacitor Networks
ECL Terminators and Line Terminator, Conformal Coated, SIP

DIMENSIONS in inches [millimeters]



Pin #1 is extreme left-hand terminal on side with marking.

NUMBER OF PINS	L MAXIMUM	NUMBER OF PINS	L MAXIMUM	NUMBER OF PINS	L MAXIMUM	NUMBER OF PINS	L MAXIMUM	NUMBER OF PINS	L MAXIMUM
4 pin	0.400 [10.16]	7 pin	0.700 [17.78]	10 pin	1.000 [25.40]	13 pin	1.300 [33.02]	16 pin	1.600 [40.64]
5 pin	0.500 [12.70]	8 pin	0.800 [20.32]	11 pin	1.100 [27.94]	14 pin	1.400 [35.56]	17 pin	1.700 [43.18]
6 pin	0.600 [15.24]	9 pin	0.900 [22.86]	12 pin	1.200 [30.48]	15 pin	1.500 [38.10]	18 pin	1.800 [45.72]



TECHNICAL SPECIFICATIONS	
Flammability:	UL 94V-0
Lead Material:	Phosphorus-bronze, solder plated
Body Material:	Epoxy coated
Solderability:	Per MIL-STD-202, Method 208E
Part Marking:	Pin #1 identification, part number (abbreviated as space allows), DALE® or D, date code
Moisture Resistance:	Meets requirements of MIL-STD-202, Method 106

PERFORMANCE		
TEST	CONDITION	MAX. ΔR (Typical Test Lots)
Thermal Shock	Subject to 5 cycles from - 65 °C to + 125 °C	± 0.5 % ΔR
Short Time Overload	2.5 x rated working voltage for 5 s at + 25 °C	± 0.25 % ΔR
Moisture Resistance	Cycle from + 25 °C to + 65 °C to + 25 °C over 8 h at 90 - 98 % relative humidity, with 10 % of rated power applied, for 20 cycles. Stop cycling after an even number of cycles and stabilize networks at high humidity for 1 to 4 h. Condition networks at - 10 °C for 3 h, then return to temperature cycling. On completion of cycling condition networks at + 25 °C at 50 % r.h. for 22 to 24 h	± 0.5 % ΔR
Resistance to Soldering Heat	Immerse pins in melted solder to the lead standoffs at + 350 °C for 3 s max.	± 0.25 % ΔR
Mechanical Shock	18 shocks of 100 G and 6 ms	± 0.25 % ΔR
Vibration	12 cycles varied logarithmically from 10 Hz to 2000 Hz to 10 Hz over 20 min	± 0.25 % ΔR
Load Life	1000 h at + 70 °C, rated power applied 1.5 h "ON", 0.5 h "OFF"	± 1.0 % ΔR
Resistance to Solvents	Immerse and scrub samples with isopropyl alcohol, trichlorethylene and Freon TMC	Marking remains legible
Solderability	Immerse leads in 60/40 tin-lead solder using R flux at + 245 °C for 5 s maximum	Minimum 95 % solder coverage
Terminal Strength	Withstand 2.2 kg pull 1 min	± 0.25 % ΔR
Case Insulation Resistance	100 V applied between case and terminals tied together	IR = 10 000 MΩ minimum



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.