


### Features

- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTA)
- Built-In Biasing Resistors, R1≠R2
- Lead Free/RoHS Compliant (Note 2)

### Mechanical Data


- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Terminal Connections: See Diagram
- Marking: Date Code and Marking Code (See Table Below & Page 3)
- Ordering Information (See Page 2)
- Weight: 0.008 grams (approximate)




| SOT-23 |       |       |
|--------|-------|-------|
| Dim    | Min   | Max   |
| A      | 0.37  | 0.51  |
| B      | 1.20  | 1.40  |
| C      | 2.30  | 2.50  |
| D      | 0.89  | 1.03  |
| E      | 0.45  | 0.60  |
| G      | 1.78  | 2.05  |
| H      | 2.80  | 3.00  |
| J      | 0.013 | 0.10  |
| K      | 0.903 | 1.10  |
| L      | 0.45  | 0.61  |
| M      | 0.085 | 0.180 |
| α      | 0°    | 8°    |

All Dimensions in mm

| P/N        | R1 (NOM) | R2 (NOM) | Type Code |
|------------|----------|----------|-----------|
| DDTC113ZCA | 1KΩ      | 10KΩ     | N02       |
| DDTC123YCA | 2.2KΩ    | 10KΩ     | N05       |
| DDTC123JCA | 2.2KΩ    | 47KΩ     | N06       |
| DDTC143XCA | 4.7KΩ    | 10KΩ     | N09       |
| DDTC143FCA | 4.7KΩ    | 22KΩ     | N10       |
| DDTC143ZCA | 4.7KΩ    | 47KΩ     | N11       |
| DDTC114YCA | 10KΩ     | 47KΩ     | N14       |
| DDTC114WCA | 10KΩ     | 4.7KΩ    | N15       |
| DDTC124XCA | 22KΩ     | 47KΩ     | N18       |
| DDTC144VCA | 47KΩ     | 10KΩ     | N21       |
| DDTC144WCA | 47KΩ     | 22KΩ     | N22       |



Schematic and Pin Configuration



Equivalent Inverter Circuit

### Maximum Ratings @ TA = 25°C unless otherwise specified

| Characteristic                                       | Symbol                            | Value   | Unit |
|--|-----------------------------------|---|------|
| Supply Voltage, (3) to (2)                           | V <sub>CC</sub>                   | 50  | V    |
| Input Voltage, (1) to (2)                            | V <sub>IN</sub>                   | -5 to +10<br>-5 to +12<br>-5 to +12<br>-7 to +20<br>-6 to +30<br>-5 to +30<br>-6 to +40<br>-10 to +30<br>-10 to +40<br>-10 to +40<br>-15 to +40<br>-10 to +40 | V    |
| Output Current                                       | I <sub>O</sub>                    | 100<br>100<br>100<br>100<br>100<br>100<br>70<br>100<br>50<br>30<br>30   | mA   |
| Output Current                                       | I <sub>C</sub> (Max)              | 100   | mA   |
| Power Dissipation                                    | P <sub>d</sub>                    | 200   | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 1) | R <sub>θJA</sub>                  | 625   | °C/W |
| Operating and Storage and Temperature Range          | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150   | °C   |

Note: 1. Mounted on FR4 PC Board with recommended pad layout which can be found at <http://www.diodes.com/datasheets/ap02001.pdf>.  
2. No purposefully added lead.

### Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic             |  | Symbol                          | Min   | Typ | Max  | Unit | Test Condition  |  |
|----------------------------|--|---------------------------------|---|-----|--|------|---|--|
| Input Voltage              | DDTC113ZCA<br>DDTC123YCA<br>DDTC123JCA<br>DDTC143XCA<br>DDTC143FCA<br>DDTC143ZCA<br>DDTC114YCA<br>DDTC114WCA<br>DDTC124XCA<br>DDTC144VCA<br>DDTC144WCA | V <sub>I(off)</sub>             | 0.3<br>0.3<br>0.5<br>0.3<br>0.3<br>0.5<br>0.3<br>0.8<br>0.4<br>1.0<br>0.8 | —   | —  | —    | V   | V <sub>CC</sub> = 5V, I <sub>O</sub> = 100μA   |
|                            | DDTC113ZCA<br>DDTC123YCA<br>DDTC123JCA<br>DDTC143XCA<br>DDTC143FCA<br>DDTC143ZCA<br>DDTC114YCA<br>DDTC114WCA<br>DDTC124XCA<br>DDTC144VCA<br>DDTC144WCA | V <sub>I(on)</sub>              | —   | —   | 3.0<br>3.0<br>1.1<br>2.5<br>1.3<br>1.3<br>1.4<br>3.0<br>2.5<br>5.0<br>4.0      | —    | V   | V <sub>O</sub> = 0.3V, I <sub>O</sub> = 20mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 20mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 20mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 3mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 1mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 2mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 2mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 2mA<br>V <sub>O</sub> = 0.3V, I <sub>O</sub> = 2mA |
| Output Voltage             |  | V <sub>O(on)</sub>              | —   | 0.1 | 0.3  | V    | I <sub>O</sub> /I <sub>I</sub> = 5mA/0.25mA DDCT123JCA<br>I <sub>O</sub> /I <sub>I</sub> = 5mA/0.25mA DDCT143ZCA<br>I <sub>O</sub> /I <sub>I</sub> = 5mA/0.25mA DDCT114YCA<br>I <sub>O</sub> /I <sub>I</sub> = 10mA/0.5mA All Others  |  |
| Input Current              | DDTC113ZCA<br>DDTC123YCA<br>DDTC123JCA<br>DDTC143XCA<br>DDTC143FCA<br>DDTC143ZCA<br>DDTC114YCA<br>DDTC114WCA<br>DDTC124XCA<br>DDTC144VCA<br>DDTC144WCA | I <sub>I</sub>                  | —   | —   | 7.2<br>3.8<br>3.6<br>1.8<br>1.8<br>1.8<br>0.88<br>0.88<br>0.36<br>0.16<br>0.16 | mA   | V <sub>I</sub> = 5V   |  |
| Output Current             |  | I <sub>O(off)</sub>             | —   | —   | 0.5  | μA   | V <sub>CC</sub> = 50V, V <sub>I</sub> = 0V  |  |
| DC Current Gain            | DDTC113ZCA<br>DDTC123YCA<br>DDTC123JCA<br>DDTC143XCA<br>DDTC143FCA<br>DDTC143ZCA<br>DDTC114YCA<br>DDTC114WCA<br>DDTC124XCA<br>DDTC144VCA<br>DDTC144WCA | G <sub>I</sub>                  | 33<br>33<br>80<br>30<br>68<br>80<br>68<br>24<br>68<br>33<br>56            | —   | —  | —    | V <sub>O</sub> = 5V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 10mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 5mA<br>V <sub>O</sub> = 5V, I <sub>O</sub> = 5mA |  |
| Input Resistor Tolerance   |  | ΔR <sub>1</sub>                 | -30   | —   | +30  | %    | —   |  |
| Resistance Ratio Tolerance |  | ΔR <sub>2</sub> /R <sub>1</sub> | -20   | —   | +20  | %    | —   |  |
| Gain-Bandwidth Product*    |  | f <sub>T</sub>                  | —   | 250 | —  | MHz  | V <sub>CE</sub> = 10V, I <sub>E</sub> = 5mA,<br>f = 100MHz  |  |


\* Transistor - For Reference Only

### Ordering Information (Note 3)

| Device         | Packaging | Shipping         |
|----------------|-----------|------------------|
| DDTC113ZCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC123YCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC123JCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC143XCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC143FCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC143ZCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC114YCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC114WCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC124XCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC144VCA-7-F | SOT-23    | 3000/Tape & Reel |
| DDTC144WCA-7-F | SOT-23    | 3000/Tape & Reel |

Note: 3. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



NXX = Product Type Marking Code, See Table on Page 1  
 YM = Date Code Marking  
 Y = Year ex: T = 2006  
 M = Month ex: 9 = September

Date Code Key

| Year | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 | 2011 | 2012 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| Code | N    | P    | R    | S    | T    | U    | V    | W    | X    | Y    | Z    |

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3   | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |



**TYPICAL CURVES - DDTC123JCA**




Fig. 1 Derating Curve




Fig. 2  $V_{CE(SAT)}$  vs.  $I_C$




Fig. 3 DC Current Gain




Fig. 4 Output Capacitance




Fig. 5 Collector Current Vs. Input Voltage




Fig. 6 Input Voltage vs. Collector Current

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.

EEPW 电子產品世界  
.com.cn