



A Schlumberger Company

FDH600/FDLL600 FDH666/FDLL666

Ultra Fast Diodes

T-03-09

- C... 2.5 pF (MAX) FDH600, 3.5 pF (MAX) FDH666
- V_F... 1.0 V (MAX) @ 100 mA (FDH666)
... 1.0 V (MAX) @ 200 mA (FDH600)
- t_{rr}... 4.0 ns (MAX) @ I_f = I_r = 10 mA

PACKAGES

FDH600	DO-35
FDH666	DO-35
FDLL600	LL-34
FDLL666	LL-34

ABSOLUTE MAXIMUM RATINGS (Note 1)**Temperatures**

Storage Temperature Range
Maximum Junction Operating Temperature
Lead Temperature

-65°C to +200°C
+175°C
+260°C

If you need this device in the SOT package, an electrical equivalent is available. See FDSO1200 family.

Power Dissipation (Note 2)

Maximum Total Dissipation at 25°C Ambient
Linear Derating Factor (from 25°C)

500 mW
3.33 mW/°C

Maximum Voltage and Currents

WIV	Working Inverse Voltage	FDH 600	FDH 666
I _O	Average Rectified Current	50 V	25 V
I _F	Continuous Forward Current	200 mA	200 mA
I _f	Recurrent Peak Forward Current	500 mA	500 mA
I _{f(surge)}	Peak Forward Surge Current	600 mA	600 mA
Pulse Width = 1.0 s			
Pulse Width = 1.0 μs			

FDH 600	FDH 666
50 V	25 V
200 mA	200 mA
500 mA	500 mA
600 mA	600 mA
1.0 A	1.0 A
4.0 A	4.0 A

ELECTRICAL CHARACTERISTICS (25°C Ambient Temperature unless otherwise noted)

SYMBOL	CHARACTERISTIC	FDH600		FDH666		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
V _F	Forward Voltage			1.0 0.92 0.86 0.79 0.65		V	I _F = 200 mA I _F = 100 mA I _F = 50 mA I _F = 10 mA I _F = 1.0 mA
I _R	Reverse Current			0.1 100	0.1 100	μA μA μA μA	V _R = 50 V V _R = 25 V V _R = 50 V, TA = 150°C V _R = 25 V, TA = 160°C
BV	Breakdown Voltage	75		40		V	I _R = 5.0 μA
t _{rr}	Reverse Recovery Time (Note 3)			4.0 6.0	4.0 6.0	ns ns	I _f = I _r = 10 mA, R _L = 100 Ω I _f = I _r = 200 mA, R _L = 100 Ω
C	Capacitance			2.5	3.5	pF	V _R = 0, f = 1.0 MHz

NOTES:

1. The maximum ratings are limiting values above which life or satisfactory performance may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty-cycle operation.
3. Recovery to 0.1 I_f.
4. For product family characteristic curves, refer to Chapter 4, D4.