



## FDG6303N Dual N-Channel, Digital FET

### General Description

These dual N-Channel logic level enhancement mode field effect transistors are produced using Fairchild's proprietary, high cell density, DMOS technology. This very high density process is especially tailored to minimize on-state resistance. This device has been designed especially for low voltage applications as a replacement for bipolar digital transistors and small signal MOSFETs.

### Features

- 25 V, 0.50 A continuous, 1.5 A peak.  
 $R_{DS(ON)} = 0.45 \Omega @ V_{GS} = 4.5 V$ ,  
 $R_{DS(ON)} = 0.60 \Omega @ V_{GS} = 2.7 V$ .
- Very low level gate drive requirements allowing direct operation in 3 V circuits ( $V_{GS(th)} < 1.5 V$ ).
- Gate-Source Zener for ESD ruggedness (>6kV Human Body Model).
- Compact industry standard SC70-6 surface mount package.



\* The pinouts are symmetrical; pin 1 and 4 are interchangeable.  
Units inside the carrier can be of either orientation and will not affect the functionality of the device.

### Absolute Maximum Ratings $T_A = 25^\circ\text{C}$ unless otherwise noted

| Symbol         | Parameter  | FDG6303N     | Units            |
|----------------|--|--------------|------------------|
| $V_{DS}$       | Drain-Source Voltage   | 25           | V                |
| $V_{GS}$       | Gate-Source Voltage  | -0.5 to +8   | V                |
| $I_D$          | Drain/Output Current   | - Continuous | 0.5              |
|                |  | - Pulsed     | 1.5              |
| $P_D$          | Maximum Power Dissipation (Note 1)   | 0.3          | W                |
| $T_J, T_{STG}$ | Operating and Storage Temperature Range  | -55 to 150   | $^\circ\text{C}$ |
| ESD            | Electrostatic Discharge Rating MIL-STD-883D Human Body Model (100 pF / 1500 $\Omega$ ) | 6.0          | kV               |

### THERMAL CHARACTERISTICS

|                 |   |     |                    |
|-----------------|---|-----|--------------------|
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | 415 | $^\circ\text{C/W}$ |
|-----------------|---|-----|--------------------|

## Electrical Characteristics (T<sub>A</sub> = 25 °C unless otherwise noted )

| Symbol  | Parameter                               | Conditions  | Min  | Typ  | Max  | Units |
|---|---|---|------|------|------|-------|
| <b>OFF CHARACTERISTICS</b>                                    |   |   |      |      |      |       |
| BV <sub>DSS</sub>   | Drain-Source Breakdown Voltage          | V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA                            | 25   |      |      | V     |
| ΔBV <sub>DSS</sub> /ΔT <sub>J</sub>                           | Breakdown Voltage Temp. Coefficient     | I <sub>D</sub> = 250 μA, Referenced to 25°C                               |      | 26   |      | mV/°C |
| I <sub>DSS</sub>  | Zero Gate Voltage Drain Current         | V <sub>DS</sub> = 20 V, V <sub>GS</sub> = 0 V                             |      |      | 1    | μA    |
|   |   | T <sub>J</sub> = 55°C   |      |      | 10   | μA    |
| I <sub>GSS</sub>  | Gate - Body Leakage Current             | V <sub>GS</sub> = 8 V, V <sub>DS</sub> = 0 V                              |      |      | 100  | nA    |
| <b>ON CHARACTERISTICS (Note 2)</b>                            |   |   |      |      |      |       |
| V <sub>GS(th)</sub>   | Gate Threshold Voltage                  | V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 μA               | 0.65 | 0.8  | 1.5  | V     |
| ΔV <sub>GS(th)</sub> /ΔT <sub>J</sub>                         | Gate Threshold Voltage Temp.Coefficient | I <sub>D</sub> = 250 μA, Referenced to 25°C                               |      | -2.6 |      | mV/°C |
| R <sub>DS(on)</sub>   | Static Drain-Source On-Resistance       | V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 0.5 A                           |      | 0.34 | 0.45 | Ω     |
|   |   | T <sub>J</sub> = 125°C  |      | 0.55 | 0.77 |       |
|   |   | V <sub>GS</sub> = 2.7 V, I <sub>D</sub> = 0.2 A                           |      | 0.44 | 0.6  |       |
| I <sub>D(on)</sub>  | On-State Drain Current                  | V <sub>GS</sub> = 2.7 V, V <sub>DS</sub> = 5 V                            | 0.5  |      |      | A     |
| g <sub>FS</sub>   | Forward Transconductance                | V <sub>DS</sub> = 5 V, I <sub>D</sub> = 0.5 A                             |      | 1.45 |      | S     |
| <b>DYNAMIC CHARACTERISTICS</b>                                |   |   |      |      |      |       |
| C <sub>iss</sub>  | Input Capacitance                       | V <sub>DS</sub> = 10 V, V <sub>GS</sub> = 0 V,<br>f = 1.0 MHz             |      | 50   |      | pF    |
| C <sub>oss</sub>  | Output Capacitance                      |   |      | 28   |      | pF    |
| C <sub>rss</sub>  | Reverse Transfer Capacitance            |   |      | 9    |      | pF    |
| <b>SWITCHING CHARACTERISTICS (Note 2)</b>                     |   |   |      |      |      |       |
| t <sub>D(on)</sub>  | Turn - On Delay Time                    | V <sub>DD</sub> = 5 V, I <sub>D</sub> = 0.5 A,                            |      | 3    | 6    | ns    |
| t <sub>r</sub>  | Turn - On Rise Time                     | V <sub>GS</sub> = 4.5 V, R <sub>GEN</sub> = 50 Ω                          |      | 8.5  | 18   |       |
| t <sub>D(off)</sub>   | Turn - Off Delay Time                   |   |      | 17   | 30   |       |
| t <sub>f</sub>  | Turn - Off Fall Time                    |   |      | 13   | 25   |       |
| Q <sub>g</sub>  | Total Gate Charge                       | V <sub>DS</sub> = 5 V, I <sub>D</sub> = 0.5 A,<br>V <sub>GS</sub> = 4.5 V |      | 1.64 | 2.3  |       |
| Q <sub>gs</sub>   | Gate-Source Charge                      |   |      | 0.38 |      | nC    |
| Q <sub>gd</sub>   | Gate-Drain Charge                       |   |      | 0.45 |      | nC    |
| <b>DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS</b> |   |   |      |      |      |       |
| I <sub>S</sub>  | Maximum Continuous Source Current       |   |      |      | 0.25 | A     |
| V <sub>SD</sub>   | Drain-Source Diode Forward Voltage      | V <sub>GS</sub> = 0 V, I <sub>S</sub> = 0.25 A (Note 2)                   |      | 0.8  | 1.2  | V     |

### Notes:

- R<sub>θJA</sub> is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins. R<sub>θJC</sub> is guaranteed by design while R<sub>θCA</sub> is determined by the user's board design. R<sub>θJA</sub> = 415°C/W on minimum pad mounting on FR-4 board in still air.
- Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2.0%.

## Typical Electrical Characteristics




Figure 1. On-Region Characteristics.




Figure 2. On-Resistance Variation with Drain Current and Gate Voltage.




Figure 3. On-Resistance Variation with Temperature.




Figure 4. On-Resistance Variation with Gate-to-Source Voltage.




Figure 5. Transfer Characteristics.




Figure 6. Body Diode Forward Voltage Variation with Source Current and Temperature.

## Typical Electrical Characteristics (continued)




Figure 7. Gate Charge Characteristics.




Figure 8. Capacitance Characteristics.




Figure 9. Maximum Safe Operating Area.




Figure 10. Single Pulse Maximum Power Dissipation.




Figure 11. Transient Thermal Response Curve.

Thermal characterization performed using the conditions described in note 1.  
Transient thermal response will change depending on the circuit board design.

## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                      |                     |                    |                     |                 |
|--------------------------------------|---------------------|--------------------|---------------------|-----------------|
| ACEx™                                | FACT™               | ImpliedDisconnect™ | PACMAN™             | SPM™            |
| ActiveArray™                         | FACT Quiet Series™  | ISOPLANAR™         | POP™                | Stealth™        |
| Bottomless™                          | FAST®               | LittleFET™         | Power247™           | SuperSOT™-3     |
| CoolFET™                             | FASTr™              | MicroFET™          | PowerTrench®        | SuperSOT™-6     |
| CROSSVOLT™                           | FRFET™              | MicroPak™          | QFET™               | SuperSOT™-8     |
| DOME™                                | GlobalOptoisolator™ | MICROWIRE™         | QS™                 | SyncFET™        |
| EcoSPARK™                            | GTO™                | MSX™               | QT Optoelectronics™ | TinyLogic®      |
| E <sup>2</sup> CMOS™                 | HiSeC™              | MSXPro™            | Quiet Series™       | TruTranslation™ |
| EnSigna™                             | I <sup>2</sup> C™   | OCX™               | RapidConfigure™     | UHC™            |
| Across the board. Around the world.™ |                     | OCXPro™            | RapidConnect™       | UltraFET®       |
| The Power Franchise™                 |                     | OPTOLOGIC®         | SILENT SWITCHER®    | VCX™            |
| Programmable Active Droop™           |                     | OPTOPLANAR™        | SMART START™        |                 |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition  |
|--------------------------|------------------------|---|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.  |
| Preliminary              | First Production       | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.   |