

---

# HZ-P Series

Silicon Epitaxial Planar Zener Diodes  
for Voltage Controller & Voltage Limiter

# HITACHI

ADE-208-123D (Z)

Rev.4  
Sep. 2000

---


## Features

- Wide spectrum from 1.88V through 40V of zener voltage provide flexible application.
- Glass package DO-41 structure ensures high reliability.

## Ordering Information

| Type No.    | Mark     | Package Code |
|-------------|----------|--------------|
| HZ-P Series | Type No. | DO-41        |

## Outline



## HZ-P Series

### Absolute Maximum Ratings

(Ta = 25°C)

| Item                 | Symbol | Value       | Unit |
|----------------------|--------|-------------|------|
| Power dissipation    | Pd     | 0.8         | W    |
| Junction temperature | Tj     | 175         | °C   |
| Storage temperature  | Tstg   | -55 to +175 | °C   |

### Electrical Characteristics

(Ta = 25°C)

| Type  | Grade | Zener Voltage                    |      | Reverse Current     |                     | Dynamic Resistance |                    |                     |
|-------|-------|----------------------------------|------|---------------------|---------------------|--------------------|--------------------|---------------------|
|       |       | V <sub>z</sub> (V)* <sup>1</sup> |      | Test Condition      | I <sub>R</sub> (μA) | Test Condition     | r <sub>d</sub> (Ω) | Test Condition      |
|       |       | Min                              | Max  | I <sub>z</sub> (mA) | Max                 | V <sub>R</sub> (V) | Max                | I <sub>z</sub> (mA) |
| HZ2.0 | BP    | 1.88                             | 2.12 | 40                  | 200                 | 0.5                | 25                 | 40                  |
|       | CP    | 2.00                             | 2.24 |                     |                     |                    |                    |                     |
| HZ2.2 | BP    | 2.08                             | 2.33 | 40                  | 200                 | 0.7                | 20                 | 40                  |
|       | CP    | 2.20                             | 2.45 |                     |                     |                    |                    |                     |
| HZ2.4 | BP    | 2.28                             | 2.56 | 40                  | 200                 | 1.0                | 15                 | 40                  |
|       | CP    | 2.40                             | 2.70 |                     |                     |                    |                    |                     |
| HZ2.7 | BP    | 2.5                              | 2.9  | 40                  | 200                 | 1.0                | 15                 | 40                  |
|       | CP    | 2.7                              | 3.1  |                     |                     |                    |                    |                     |
| HZ3.0 | BP    | 2.8                              | 3.2  | 40                  | 100                 | 1.0                | 15                 | 40                  |
|       | CP    | 3.0                              | 3.4  |                     |                     |                    |                    |                     |
| HZ3.3 | BP    | 3.1                              | 3.5  | 40                  | 80                  | 1.0                | 15                 | 40                  |
|       | CP    | 3.3                              | 3.7  |                     |                     |                    |                    |                     |
| HZ3.6 | BP    | 3.4                              | 3.8  | 40                  | 60                  | 1.0                | 15                 | 40                  |
|       | CP    | 3.6                              | 4.0  |                     |                     |                    |                    |                     |
| HZ3.9 | BP    | 3.7                              | 4.1  | 40                  | 40                  | 1.0                | 15                 | 40                  |
|       | CP    | 3.9                              | 4.4  |                     |                     |                    |                    |                     |
| HZ4.3 | BP    | 4.0                              | 4.5  | 40                  | 20                  | 1.0                | 15                 | 40                  |
|       | CP    | 4.3                              | 4.8  |                     |                     |                    |                    |                     |
| HZ4.7 | BP    | 4.4                              | 4.9  | 40                  | 20                  | 1.0                | 10                 | 40                  |
|       | CP    | 4.7                              | 5.2  |                     |                     |                    |                    |                     |

Note: 1. Tested with DC.

**Electrical Characteristics (cont)**

(Ta = 25°C)

| Type  | Grade | Zener Voltage |      | Reverse Current |                  | Dynamic Resistance |                    |                |
|-------|-------|---------------|------|-----------------|------------------|--------------------|--------------------|----------------|
|       |       | $V_z$ (V)*1   |      | Test Condition  | $I_R$ ( $\mu$ A) | Test Condition     | $r_d$ ( $\Omega$ ) | Test Condition |
|       |       | Min           | Max  | $I_z$ (mA)      | Max              | $V_R$ (V)          | Max                | $I_z$ (mA)     |
| HZ5.1 | BP    | 4.8           | 5.4  | 40              | 20               | 1.0                | 8                  | 40             |
|       | CP    | 5.1           | 5.7  |                 |                  |                    |                    |                |
| HZ5.6 | BP    | 5.3           | 6.0  | 40              | 20               | 1.5                | 8                  | 40             |
|       | CP    | 5.6           | 6.3  |                 |                  |                    |                    |                |
| HZ6.2 | BP    | 5.8           | 6.6  | 40              | 20               | 3.0                | 6                  | 40             |
|       | CP    | 6.2           | 7.0  |                 |                  |                    |                    |                |
| HZ6.8 | BP    | 6.4           | 7.2  | 40              | 20               | 3.5                | 6                  | 40             |
|       | CP    | 6.8           | 7.7  |                 |                  |                    |                    |                |
| HZ7.5 | BP    | 7.0           | 7.9  | 40              | 20               | 4.0                | 4                  | 40             |
|       | CP    | 7.5           | 8.4  |                 |                  |                    |                    |                |
| HZ8.2 | BP    | 7.7           | 8.7  | 40              | 20               | 5.0                | 4                  | 40             |
|       | CP    | 8.2           | 9.3  |                 |                  |                    |                    |                |
| HZ9.1 | BP    | 8.5           | 9.6  | 40              | 20               | 6.0                | 6                  | 40             |
|       | CP    | 9.1           | 10.2 |                 |                  |                    |                    |                |
| HZ10  | BP    | 9.4           | 10.6 | 40              | 10               | 7.0                | 6                  | 40             |
|       | CP    | 10.0          | 11.2 |                 |                  |                    |                    |                |
| HZ11  | BP    | 10.4          | 11.6 | 20              | 10               | 8.0                | 8                  | 20             |
|       | CP    | 11.0          | 12.3 |                 |                  |                    |                    |                |
| HZ12  | BP    | 11.4          | 12.6 | 20              | 10               | 9.0                | 8                  | 20             |
|       | CP    | 12.0          | 13.5 |                 |                  |                    |                    |                |
| HZ13  | BP    | 12.4          | 14.1 | 20              | 10               | 10.0               | 10                 | 20             |
|       | CP    | 13.3          | 15.0 |                 |                  |                    |                    |                |
| HZ15  | BP    | 13.8          | 15.6 | 20              | 10               | 11.0               | 10                 | 20             |
|       | CP    | 14.7          | 16.5 |                 |                  |                    |                    |                |
| HZ16  | BP    | 15.3          | 17.1 | 20              | 10               | 12.0               | 12                 | 20             |
|       | CP    | 16.2          | 18.3 |                 |                  |                    |                    |                |
| HZ18  | BP    | 16.8          | 19.1 | 20              | 10               | 13.0               | 12                 | 20             |
|       | CP    | 18.0          | 20.3 |                 |                  |                    |                    |                |
| HZ20  | BP    | 18.8          | 21.2 | 20              | 10               | 15.0               | 14                 | 20             |
|       | CP    | 20.0          | 22.4 |                 |                  |                    |                    |                |

Note: 1. Tested with DC.

## HZ-P Series

### Electrical Characteristics (cont)

(Ta = 25°C)

| Type | Grade | Zener Voltage           |      | Reverse Current |            | Dynamic Resistance |           |                |
|------|-------|-------------------------|------|-----------------|------------|--------------------|-----------|----------------|
|      |       | $V_z$ (V)* <sup>1</sup> |      | Test Condition  | $I_R$ (μA) | Test Condition     | $r_d$ (Ω) | Test Condition |
|      |       | Min                     | Max  | $I_z$ (mA)      | Max        | $V_R$ (V)          | Max       | $I_z$ (mA)     |
| HZ22 | BP    | 20.8                    | 23.3 | 10              | 10         | 17.0               | 14        | 10             |
|      | CP    | 22.0                    | 24.5 |                 |            |                    |           |                |
| HZ24 | BP    | 22.8                    | 25.6 | 10              | 10         | 19.0               | 16        | 10             |
|      | CP    | 24.0                    | 27.6 |                 |            |                    |           |                |
| HZ27 | BP    | 25.1                    | 28.9 | 10              | 10         | 21.0               | 16        | 10             |
|      | CP    | 27.0                    | 30.8 |                 |            |                    |           |                |
| HZ30 | BP    | 28.0                    | 32.0 | 10              | 10         | 23.0               | 18        | 10             |
|      | CP    | 30.0                    | 34.0 |                 |            |                    |           |                |
| HZ33 | BP    | 31.0                    | 35.0 | 10              | 10         | 25.0               | 18        | 10             |
|      | CP    | 33.0                    | 37.0 |                 |            |                    |           |                |
| HZ36 | BP    | 34.0                    | 38.0 | 10              | 10         | 27.0               | 20        | 10             |
|      | CP    | 36.0                    | 40.0 |                 |            |                    |           |                |

Notes: 1. Tested with DC.

2. Type No. is as follows; HZ2.0BP, HZ2.0CP, ••• HZ36BP, HZ36CP.

Main Characteristic



Fig.1 Zener current Vs. Zener voltage



Fig.2 Temperature Coefficient Vs. Zener voltage




Fig.3 Power Dissipation Vs. Ambient Temperature

## HZ-P Series




Fig.4 Surge Reverse Power Ratings (Reference Data)





Fig.5 Transient Thermal Impedance

**Package Dimensions**

Unit: mm



|                        |          |
|------------------------|----------|
| Hitachi Code           | DO-41    |
| JEDEC                  | Conforms |
| EIAJ                   | Conforms |
| Mass (reference value) | 0.38 g   |

EEPW.com.cn 电子产业网

---

## HZ-P Series

---

### Disclaimer

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

### Sales Offices

---

---

# HITACHI

## Hitachi, Ltd.

Semiconductor & Integrated Circuits  
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan  
Tel: (03) 3270-2111 Fax: (03) 3270-5109

|     |               |   |
|-----|---------------|---|
| URL | North America | : <a href="http://semiconductor.hitachi.com/">http://semiconductor.hitachi.com/</a>           |
|     | Europe        | : <a href="http://www.hitachi-eu.com/hel/ecg">http://www.hitachi-eu.com/hel/ecg</a>           |
|     | Asia          | : <a href="http://sicapac.hitachi-asia.com">http://sicapac.hitachi-asia.com</a>               |
|     | Japan         | : <a href="http://www.hitachi.co.jp/Sicd/indx.htm">http://www.hitachi.co.jp/Sicd/indx.htm</a> |

### For further information write to:

Hitachi Semiconductor  
(America) Inc.  
179 East Tasman Drive  
San Jose, CA 95134  
Tel: <1> (408) 433-1990  
Fax: <1> (408) 433-0223

Hitachi Europe Ltd.  
Electronic Components Group  
Whitebrook Park  
Lower Cookham Road  
Maidenhead  
Berkshire SL6 8YA, United Kingdom  
Tel: <44> (1628) 585000  
Fax: <44> (1628) 585200

Hitachi Europe GmbH  
Electronic Components Group  
Dornacher Straße 3  
D-85622 Feldkirchen, Munich  
Germany  
Tel: <49> (89) 9 9180-0  
Fax: <49> (89) 9 29 30 00

Hitachi Asia Ltd.  
Hitachi Tower  
16 Collyer Quay #20-00  
Singapore 049318  
Tel: <65>-538-6533/538-8577  
Fax: <65>-538-6933/538-3877  
URL: <http://www.hitachi.com.sg>

Hitachi Asia Ltd.  
(Taipei Branch Office)  
4/F, No. 167, Tun Hwa North Road  
Hung-Kuo Building  
Taipei (105), Taiwan  
Tel: <886>-(2)-2718-3666  
Fax: <886>-(2)-2718-8180  
Telex: 23222 HAS-TP  
URL: <http://www.hitachi.com.tw>

Hitachi Asia (Hong Kong) Ltd.  
Group III (Electronic Components)  
7/F., North Tower  
World Finance Centre,  
Harbour City, Canton Road  
Tsim Sha Tsui, Kowloon  
Hong Kong  
Tel: <852>-(2)-735-9218  
Fax: <852>-(2)-730-0281  
URL: <http://semiconductor.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2001. All rights reserved. Printed in Japan.  
Colophon 4.0