


LOW NOISE AMPLIFIER APPLICATION.

FEATURES

- Excellent h_{FE} Linearity
: $h_{FE}(0.1mA)/h_{FE}(2mA)=0.95(\text{Typ.})$.
- Low Noise : $NF=0.2\text{dB}(\text{Typ.})$, $3\text{dB}(\text{Max.})$.
- Complementary to KTC3199L.

MAXIMUM RATINGS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CBO}	-50	V
Collector-Emitter Voltage	V_{CEO}	-50	V
Emitter-Base Voltage	V_{EBO}	-5	V
Collector Current	I_C	-150	mA
Emitter Current	I_E	150	mA
Collector Power Dissipation	P_C	400	mW
Junction Temperature	T_j	150	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-55~150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_a=25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CBO}	$V_{CB}=-50\text{V}$, $I_E=0$	-	-	-0.1	μA
Emitter Cut-off Current	I_{EBO}	$V_{EB}=-5\text{V}$, $I_C=0$	-	-	-0.1	μA
DC Current Gain	h_{FE} (Note)	$V_{CE}=-6\text{V}$, $I_C=-2\text{mA}$	70	-	400	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-100\text{mA}$, $I_B=-10\text{mA}$	-	-0.1	-0.3	V
Transition Frequency	f_T	$V_{CE}=-10\text{V}$, $I_C=-1\text{mA}$	80	-	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=-10\text{V}$, $I_E=0$, $f=1\text{MHz}$	-	4.0	7.0	pF
Noise Figure	NF(1)	$V_{CE}=-6\text{V}$, $I_C=-0.1\text{mA}$, $f=100\text{Hz}$, $R_g=10\text{k}\Omega$	-	0.5	6.0	dB
	NF(2)	$V_{CE}=-6\text{V}$, $I_C=-0.1\text{mA}$, $f=1\text{kHz}$, $R_g=10\text{k}\Omega$	-	0.2	3.0	

Note : h_{FE} Classification O:70~140, Y:120~240, GR:200~400

KTA1267L

