


FEATURES

- Surge overload rating: 200A peak
- High case dielectric strength

MECHANICAL DATA

- Terminal:** Plated leads solderable per MIL-STD 202E, method 208C
- Case:** UL-94 Class V-0 recognized Flame Retardant Epoxy
- Polarity:** Polarity symbol marked on body
- Mounting :** Hole thru for #6 screw

KBPC10



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Single-phase, half-wave, 60HZ, resistive or inductive load rating at 25 °C , unless otherwise stated, for capacitive load, derate current by 20%)

	SYMBOL	KBPC 10005	KBPC 1001	KBPC 1002	KBPC 1004	KBPC 1006	KBPC 1008	KBPC 1010	units	
Maximum Recurrent Peak Reverse Voltage	V _{rrm}	50	100	200	400	600	800	1000	V	
Maximum RMS Voltage	V _{rms}	35	70	140	280	420	560	700	V	
Maximum DC blocking Voltage	V _{dc}	50	100	200	400	600	800	1000	V	
Maximum Average Forward Rectified current at Ta=25 °C	I _{f(av)}					10.0				A
						6.0				A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{fsm}					200				A
Maximum Instantaneous Forward Voltage at forward current 5.0A DC	V _f					1.1				V
Maximum DC Reverse Voltage Ta=25 °C	I _r					10.0				μ A
at rated DC blocking voltage Ta=100 °C						200				μ A
Operating Temperature Range	T _j					-55 to +125				°C
Storage and operation Junction Temperature	T _{stg}					-55 to +150				°C

RATINGS AND CHARACTERISTIC CURVES KBPC10005 THRU KBPC1010

FIG.1-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS

