


# High Voltage, Photo <sup>EMOS</sup> Relay

**KAQV414/414A**

UL 1577/ UL 508 (File No.E108430), FI EN60950 (File No.FI13698)


## Features

1. Normally Close, Single Pole Single Throw
2. Control 400VAC or DC Voltage
3. Switch 130mA Loads
4. LED control Current, 5mA
5. Low ON-Resistance
6. dv/dt, >500V/ms
7. Isolation Test Voltage, 3750VACrms




## Absolute Maximum Ratings (Ta=25°C)

Emitter (Input)	Detector (Output)
Reverse Voltage.....5.0V	Output Breakdown Voltage .....±400V
Continuous Forward Current .....50mA	Continuous Load Current .....±130mA
Peak Forward Current .....1A	Power Dissipation .....500mW
Power Dissipation .....100mW	
Derate Linearly from 25°C .....1.3mW/°C	



## General Characteristics

Isolation Test Voltage .....3750VACrms	Storage Temperature Range ...-40°C to +125°C
Isolation Resistance	Operating Temperature Range ...-30°C to +85°C
Vio=500V, Ta=25°C .....≥10 <sup>10</sup> Ω	Junction Temperature .....100°C
Total Power Dissipation .....550mW	Soldering Temperature, 2mm from case, 10 sec .....260°C
Derate Linearly from 25°C .....2.5mW/°C	



## Electro-optical Characteristics (Ta=25°C)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Emitter (Input)						
Forward Voltage	VF	IF =10mA		1.2	1.5	V
Operation Input Current	I <sub>OFF</sub>	VL =±20V, IL ≤5uA			5	mA
Recovery Input Current	I <sub>ON</sub>	VL =±20V, IL =100mA, t =10mS	0.2			mA
Detector (Output)						
Output Breakdown Voltage	VB	IB=50uA	400			V
Output Off-State Leakage	I <sub>OFF</sub>	VT =100V, IF =10mA		0.2	2	uA
I/O Capacitance	C <sub>ISO</sub>	IF =0, f =1MHz		6		pF
ON Resistance	RON	IL =100mA, IF =10mA		40	50	Ω
				20	25	
				10	12.5	
Reverse (ON) Time	T <sub>ON</sub>	IF =10mA, VL =±20V		0.6	1.5	ms
Operate (OFF) Time	T <sub>OFF</sub>	t =10ms, IL =±100mA		0.3	1.0	ms

## Mos Relay Schematic and Wiring Diagrams

Type	Schematic	Output configuration	Load	Connection	Wiring Diagrams
KAQV414 & KAQV414A		1a	AC/DC	A	

# KAQV414/414A

## Data Curve

