

# KBPC3500 - KBPC3510

**PRV : 50 - 1000 Volts**

**Io : 35 Amperes**


### FEATURES :

- \* High current capability
- \* High surge current capability
- \* High reliability
- \* Low reverse current
- \* Low forward voltage drop
- \* **Pb / RoHS Free**

### MECHANICAL DATA :

- \* Case : Metal Case
- \* Epoxy : UL94V-O rate flame retardant
- \* Terminals : plated .25" (6.35 mm). Faston
- \* Polarity : Polarity symbols marked on case
- \* Mounting position : Bolt down on heat-sink with silicone thermal compound between bridge and mounting surface for maximum heat transfer efficiency.
- \* Weight : 17.1 grams

# SILICON BRIDGE RECTIFIERS



### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.  
 Single phase, half wave, 60 Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%.


RATING	SYMBOL	KBPC 3500	KBPC 3501	KBPC 3502	KBPC 3504	KBPC 3506	KBPC 3508	KBPC 3510	UNIT
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Current $T_c = 55^\circ C$	$I_{F(AV)}$					35			A
Peak Forward Surge Current Single half sine wave Superimposed on rated load (JEDEC Method)	$I_{FSM}$					400			A
Current Squared Time at $t < 8.3$ ms.	$I^2 t$					660			$A^2 S$
Maximum Forward Voltage per Diode at $I_F = 17.5$ A	$V_F$					1.1			V
Maximum DC Reverse Current at Rated DC Blocking Voltage	$I_R$					10			$\mu A$
	$I_{R(H)}$					200			$\mu A$
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$					1.5			$^\circ C/W$
Typical Thermal Resistance at Junction to Ambient	$R_{\theta JA}$					10			$^\circ C$
Operating Junction Temperature Range	$T_J$					- 40 to + 150			$^\circ C$
Storage Temperature Range	$T_{STG}$					- 40 to + 150			$^\circ C$

**Note :**


1. Thermal Resistance from junction to case with units mounted on a 7.5" x 3.5" x 4.6" (19cm.x 9cm.x 11.8cm.) Al.-Finned Plate

### RATING AND CHARACTERISTIC CURVES ( KBPC3500 - KBPC3510 )


**FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT**



**FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT**



**FIG.3 - TYPICAL FORWARD CHARACTERISTICS PER DIODE**



**FIG.4 - TYPICAL REVERSE CHARACTERISTICS PER DIODE**

