



## MC34072

## LINEAR INTEGRATED CIRCUIT

### HIGH SLEW RATE, WIDE BANDWIDTH , SINGLE SUPPLY OPERATIONAL AMPLIFIER

#### DESCRIPTION


The UTC MC34072 offer 4.5MHz of gain bandwidth product, 13V/ $\mu$ s slew rate and fast setting time without the use of JFET device technology. Although it can be operated from split supplies, it is particularly suited for single supply operation, since the common mode input voltage range includes ground potential ( $V_{EE}$ ). With A Darlington input stage, it exhibits high input resistance, low input offset voltage and high gain. The all NPN output stage, characterized by no deadband crossover distortion and large output voltage swing, provides high capacitance drive capability, excellent phase and gain margins, low open loop high frequency output impedance and symmetrical source/sink AC frequency response.

#### FEATURES

- \* Wide bandwidth: 4.5 MHz
- \* High slew rate: 13V/ $\mu$ s
- \* Fast settling time: 1.1 $\mu$ s to 0.1%
- \* Wide single supply operation: 3.0V to 44V
- \* Wide input common mode voltage range:  
Includes Ground ( $V_{EE}$ )
- \* Low input offset voltage: 3.0mV maximum
- \* Large output voltage swing: -14.7V to +14V  
(with +-15V supplies)
- \* Large Capacitance Drive Capability: 0pF to 10,000 pF
- \* Low total harmonic distortion: 0.02%
- \* Excellent phase margin: 60°
- \* Excellent gain margin: 12dB
- \* Output short circuit protection
- \* ESD Diodes/Clamps provide input protection

#### ORDERING INFORMATION


| Order Number  |                   | Package | Packing   |
|---------------|-------------------|---------|-----------|
| Normal        | Lead Free Plating |         |           |
| MC34072-D08-T | MC34072L-D08-T    | DIP-8   | Tube      |
| MC34072-S08-R | MC34072L-S08-R    | SOP-8   | Tape Reel |
| MC34072-S08-T | MC34072L-S08-T    | SOP-8   | Tube      |



\*Pb-free plating product number: MC34072L

|  |   |
|--|---|
| <p>MC34072L-D08-R</p> <p>(1)Packing Type<br/>(2)Package Type<br/>(3)Lead Plating</p> | <p>(1) R: Tape Reel, T: Tube<br/>(2) D08: DIP-8, S08: SOP-8<br/>(3) L: Lead Free Plating Blank: Pb/Sn</p> |
|--|---|

## ■ PIN DESCRIPTION



EEPW 電子產品世界  
.com.cn

### ■ ABSOLUTE MAXIMUM RATINGS (Ta = 25°C)

| PARAMETER   | SYMBOL               | RATINGS    | UNIT |
|---|----------------------|------------|------|
| Supply Voltage (from V <sub>EE</sub> to V <sub>CC</sub> ) | V <sub>S</sub>       | +44        | V    |
| Differential Input Voltage                                | V <sub>I(DIFF)</sub> | Note 1     | V    |
| Input Voltage   | V <sub>IN</sub>      | Note 1     | V    |
| Output Short Circuit Duration (Note 2)                    | t <sub>SC</sub>      | Indefinite | sec  |
| Junction Temperature                                      | T <sub>J</sub>       | +125       | °C   |
| Operating Temperature                                     | T <sub>OPR</sub>     | -20 ~ +85  | °C   |
| Storage Temperature Range                                 | T <sub>STG</sub>     | -40~ +150  | °C   |

- Note 1. Either or both input voltages should not exceed the magnitude of V<sub>CC</sub> or V<sub>EE</sub>.  
 2. Power dissipation must be considered to ensure maximum junction temperature (T<sub>J</sub>) is not exceeded. (see Fig. 1)  
 3. Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.  
 4. The device is guaranteed to meet performance specification within 0°C~+70°C operating temperature range and assured by design from -20°C~+85°C.

### ■ ELECTRICAL CHARACTERISTICS

(V<sub>CC</sub>=+15V, V<sub>EE</sub>=-15V, R<sub>L</sub>=connected to ground, unless otherwise specified)

| PARAMETER   | SYMBOL               | TEST CONDITIONS  | MIN                                       | TYP   | MAX   | UNIT  |
|---|----------------------|--|---|-------|-------|-------|
| Input Offset Voltage                                    | V <sub>I(OFF)</sub>  | R <sub>S</sub> =100Ω, V <sub>CC</sub> =+15V, V <sub>EE</sub> =-15V, T <sub>A</sub> =+25°C          |   | 0.5   | 3.0   | mV    |
|   |                      | V <sub>CM</sub> =0V, V <sub>CC</sub> =+5V, V <sub>EE</sub> =0V, T <sub>A</sub> =+25°C              |   | 0.5   | 3.0   | mV    |
|   |                      | V <sub>OUT</sub> =0V, V <sub>CC</sub> =+15V, V <sub>EE</sub> =-15V, T <sub>A</sub> =0°C to 70°C    |   |       |       | 5.0   |
| Average Temperature Coefficient of Input Offset Voltage | ΔV <sub>IO</sub> /ΔT | R <sub>S</sub> =10Ω, V <sub>CM</sub> =0V, V <sub>OUT</sub> =0V, T <sub>A</sub> =0°C to 70°C        |   | 10    |       | μV/°C |
| Input Bias Current                                      | I <sub>I(BIAS)</sub> | V <sub>CM</sub> =0V, V <sub>OUT</sub> =0V  | T <sub>A</sub> =+25°C                     | 100   | 500   | nA    |
|   |                      |  | T <sub>A</sub> =0°C to 70°C               |       |       | 700   |
| Input Offset Current                                    | I <sub>I(OFF)</sub>  | V <sub>CM</sub> =0V, V <sub>OUT</sub> =0V  | T <sub>A</sub> =+25°C                     | 6.0   | 50    | nA    |
|   |                      |  | T <sub>A</sub> =0°C to 70°C               |       |       | 300   |
| Input Common Mode Voltage                               | V <sub>ICR</sub>     | T <sub>A</sub> =+25°C  | V <sub>EE</sub> to (V <sub>CC</sub> -1.8) |       |       | V     |
|   |                      | T <sub>A</sub> =0°C to 70°C  | V <sub>EE</sub> to (V <sub>CC</sub> -2.2) |       |       | V     |
| Large Signal Voltage Gain                               | G <sub>V</sub>       | V <sub>OUT</sub> =±10V, R <sub>L</sub> =2.0kΩ  | T <sub>A</sub> =+25°C                     | 50    | 100   | V/mV  |
|   |                      |  | T <sub>A</sub> =0°C to 70°C               | 25    |       |       |
| Output Voltage Swing (V <sub>ID</sub> =±1.0V)           | V <sub>OH</sub>      | V <sub>CC</sub> =+5.0V, V <sub>EE</sub> =0V, R <sub>L</sub> =2.0kΩ, T <sub>A</sub> =+25°C          | 3.7                                       | 4.0   |       | V     |
|   |                      | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, R <sub>L</sub> =10kΩ, T <sub>A</sub> =+25°C        | 13.6                                      | 14    |       | V     |
|   |                      | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, R <sub>L</sub> =2.0kΩ, T <sub>A</sub> =0°C to 70°C | 13.4                                      |       |       | V     |
| Output Voltage Swing (V <sub>ID</sub> =±1.0V)           | V <sub>OL</sub>      | V <sub>CC</sub> =+5.0V, V <sub>EE</sub> =0V, R <sub>L</sub> =2.0kΩ, T <sub>A</sub> =+25°C          |   | 0.1   | 0.3   | V     |
|   |                      | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, R <sub>L</sub> =10kΩ, T <sub>A</sub> =+25°C        |   | -14.7 | -14.3 | V     |
|   |                      | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, R <sub>L</sub> =2.0kΩ, T <sub>A</sub> =0°C to 70°C |   |       | -13.5 | V     |
| Output Short Circuit current                            | I <sub>SC</sub>      | V <sub>I(DIFF)</sub> =1.0V, V <sub>OUT</sub> =0V, T <sub>A</sub> =25°C                             | Source                                    | 10    | 30    | mA    |
|   |                      |  | Sink                                      | 20    | 30    |       |
| Common Mode Rejection                                   | CMR                  | R <sub>S</sub> ≤10kΩ, V <sub>CM</sub> =V <sub>ICR</sub> , T <sub>A</sub> =25°C                     | 80  | 97    |       | dB    |
| Power Supply Rejection (R <sub>S</sub> =100Ω)           | SVR                  | V <sub>CC</sub> /V <sub>EE</sub> =+16.5V/-16.5V to +13.5/-13.5V, T <sub>A</sub> =25°C              | 80  | 97    |       | dB    |

### ■ ELECTRICAL CHARACTERISTICS(Cont.)

| PARAMETER                                     | SYMBOL          | TEST CONDITIONS  | MIN     | TYP        | MAX | UNIT   |
|---|-----------------|--|---------|------------|-----|--------|
| Power Supply Current (Per Amplifier, No Load) | I <sub>D</sub>  | V <sub>CC</sub> =+5.0V, V <sub>EE</sub> =0V, V <sub>OUT</sub> =+2.5V, Ta=+25°C       |         | 1.6        | 2.0 | mA     |
|   |                 | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, V <sub>OUT</sub> =0V, Ta=+25°C       |         | 1.9        | 2.5 | mA     |
|   |                 | V <sub>CC</sub> =+15.0V, V <sub>EE</sub> =-15V, V <sub>OUT</sub> =0V, Ta=0°C to 70°C |         |            |     | 2.8    |
| Slew Rate                                     | SR              | V <sub>IN</sub> =-10V to +10V, R <sub>L</sub> =2.0kΩ, C <sub>L</sub> =500pF          | Av=+1.0 | 8.0        | 10  | V/μs   |
|   |                 |  | Av=-1.0 |            | 13  |        |
| Setting Time                                  | ts              | 10 Setp, Av=-1.0 to 0.1% (+1/2 LSB of 9-Bits) to 0.01% (+1/2 LSB of 12-Bits)         |         | 1.1<br>2.2 |     | μs     |
| Gain Bandwidth Product                        | GB <sub>W</sub> | f=100kHz   | 3.5     | 4.5        |     | MHz    |
| Power Bandwidth                               | B <sub>W</sub>  | Av=+1.0, R <sub>L</sub> =2kΩ, V <sub>OUT</sub> =20Vpp, THD=5.0%                      |         | 160        |     | kHz    |
| Phase Margin                                  | fm              | R <sub>L</sub> =2kΩ  |         | 60         |     | Deg    |
|   |                 | R <sub>L</sub> =2kΩ, C <sub>L</sub> =300pF   |         | 40         |     | Deg    |
| Gain Margin                                   | Am              | R <sub>L</sub> =2kΩ  |         | 12         |     | dB     |
|   |                 | R <sub>L</sub> =2kΩ, C <sub>L</sub> =300pF   |         | 4          |     | dB     |
| Equivalent Input Noise Voltage                | eN              | Rs=100Ω, f=1.0kHz  |         | 32         |     | nV/√Hz |
| Equivalent Input Noise Current                | eN              | f=1.0kHz   |         | 0.22       |     | pA/√Hz |
| Differential Input Resistance                 | R <sub>IN</sub> | V <sub>CM</sub> =0V  |         | 150        |     | MΩ     |
| Differential Input Capacitance                | C <sub>IN</sub> | V <sub>CM</sub> =0V  |         | 2.5        |     | pF     |
| Total Harmonic distortion                     | THD             | Av=+10, R <sub>L</sub> =2.0kΩ, 2.0Vpp ≤ V <sub>out</sub> ≤ 20Vpp, f=10kHz            |         | 0.02       |     | %      |
| Channel Separation                            |                 | f=10kHz  |         | 120        |     | dB     |
| Open Loop Output Impedance                    | Z <sub>ol</sub> | f=1.0MHz   |         | 30         |     | W      |

■ REPRESENTATIVE SCHEMATIC DIAGRAM











FIG.1







■ POWER SUPPLY CONFIGURATIONS









## TYPICAL CHARACTERISTICS



## TYPICAL CHARACTERISTICS (Cont)









## TYPICAL CHARACTERISTICS(Cont.)















## TYPICAL CHARACTERISTICS(Cont.)



## TYPICAL CHARACTERISTICS(Cont.)



## TYPICAL CHARACTERISTICS(Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.