


**SIPMOS® Power Transistor**

- N channel
- Enhancement mode
- Logic Level
- Avalanche-rated
- dv/dt rated
- 175°C operating temperature
- also in SMD available



Pin 1	Pin 2	Pin 3
G	D	S

Type	V <sub>DS</sub>	I <sub>D</sub>	R <sub>DS(on)</sub>	Package	Ordering Code
BUZ 102 SL	55 V	47 A	0.028 Ω	TO-220 AB	Q67040-S4010-A2

**Maximum Ratings**

Parameter	Symbol	Values	Unit
Continuous drain current $T_C = 25\text{ °C}$ $T_C = 100\text{ °C}$	$I_D$	47 33	A
Pulsed drain current $T_C = 25\text{ °C}$	$I_{Dpuls}$	188	
Avalanche energy, single pulse $I_D = 47\text{ A}$ , $V_{DD} = 25\text{ V}$ , $R_{GS} = 25\text{ Ω}$ $L = 222\text{ μH}$ , $T_j = 25\text{ °C}$	$E_{AS}$	245	mJ
Avalanche current, limited by $T_{jmax}$	$I_{AR}$	47	A
Avalanche energy, periodic limited by $T_{jmax}$	$E_{AR}$	12	mJ
Reverse diode dv/dt $I_S = 47\text{ A}$ , $V_{DS} = 40\text{ V}$ , $di_F/dt = 200\text{ A/μs}$ $T_{jmax} = 175\text{ °C}$	dv/dt	6	kV/μs
Gate source voltage	$V_{GS}$	± 14	V
Power dissipation $T_C = 25\text{ °C}$	$P_{tot}$	120	W

**Maximum Ratings**

Parameter	Symbol	Values	Unit
Operating temperature	$T_j$	-55 ... + 175	°C
Storage temperature	$T_{stg}$	-55 ... + 175	
Thermal resistance, junction - case	$R_{thJC}$	≤ 1.25	K/W
Thermal resistance, junction - ambient	$R_{thJA}$	≤ 62	
IEC climatic category, DIN IEC 68-1		55 / 175 / 56	

**Electrical Characteristics, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified**


Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Static Characteristics</b>					
Drain- source breakdown voltage $V_{GS} = 0 \text{ V}, I_D = 0.25 \text{ mA}, T_j = 25^\circ\text{C}$	$V_{(BR)DSS}$	55	-	-	V
Gate threshold voltage $V_{GS} = V_{DS}, I_D = 90 \mu\text{A}$	$V_{GS(th)}$	1.2	1.6	2	
Zero gate voltage drain current $V_{DS} = 50 \text{ V}, V_{GS} = 0 \text{ V}, T_j = -40^\circ\text{C}$ $V_{DS} = 50 \text{ V}, V_{GS} = 0 \text{ V}, T_j = 25^\circ\text{C}$ $V_{DS} = 50 \text{ V}, V_{GS} = 0 \text{ V}, T_j = 150^\circ\text{C}$	$I_{DSS}$	-	-	0.1 1 100	$\mu\text{A}$
Gate-source leakage current $V_{GS} = 20 \text{ V}, V_{DS} = 0 \text{ V}$	$I_{GSS}$	-	10	100	nA
Drain-Source on-resistance $V_{GS} = 4.5 \text{ V}, I_D = 33 \text{ A}$ $V_{GS} = 10 \text{ V}, I_D = 33 \text{ A}$	$R_{DS(on)}$	-	0.022 0.014	0.028 0.018	$\Omega$

**Electrical Characteristics**, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Dynamic Characteristics</b>					
Transconductance $V_{DS} \geq 2 \cdot I_D \cdot R_{DS(on)max}$ , $I_D = 33 \text{ A}$	$g_{fs}$	10	-	-	S
Input capacitance $V_{GS} = 0 \text{ V}$ , $V_{DS} = 25 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{iss}$	-	1380	1730	pF
Output capacitance $V_{GS} = 0 \text{ V}$ , $V_{DS} = 25 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{oss}$	-	410	515	
Reverse transfer capacitance $V_{GS} = 0 \text{ V}$ , $V_{DS} = 25 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{rss}$	-	230	290	
Turn-on delay time $V_{DD} = 30 \text{ V}$ , $V_{GS} = 4.5 \text{ V}$ , $I_D = 47 \text{ A}$ $R_G = 3.6 \Omega$	$t_{d(on)}$	-	15	25	ns
Rise time $V_{DD} = 30 \text{ V}$ , $V_{GS} = 4.5 \text{ V}$ , $I_D = 47 \text{ A}$ $R_G = 3.6 \Omega$	$t_r$	-	30	45	
Turn-off delay time $V_{DD} = 30 \text{ V}$ , $V_{GS} = 4.5 \text{ V}$ , $I_D = 47 \text{ A}$ $R_G = 3.6 \Omega$	$t_{d(off)}$	-	30	45	
Fall time $V_{DD} = 30 \text{ V}$ , $V_{GS} = 4.5 \text{ V}$ , $I_D = 47 \text{ A}$ $R_G = 3.6 \Omega$	$t_f$	-	20	30	
Gate charge at threshold $V_{DD} = 40 \text{ V}$ , $I_D = 0.1 \text{ A}$ , $V_{GS} = 0 \text{ to } 1 \text{ V}$	$Q_{g(th)}$	-	2	3	nC
Gate charge at 5.0 V $V_{DD} = 40 \text{ V}$ , $I_D = 47 \text{ A}$ , $V_{GS} = 0 \text{ to } 5 \text{ V}$	$Q_{g(5)}$	-	35	55	
Gate charge total $V_{DD} = 40 \text{ V}$ , $I_D = 47 \text{ A}$ , $V_{GS} = 0 \text{ to } 10 \text{ V}$	$Q_{g(total)}$	-	60	90	
Gate plateau voltage $V_{DD} = 40 \text{ V}$ , $I_D = 47 \text{ A}$	$V_{(plateau)}$	-	4.1	-	V


**Electrical Characteristics, at  $T_j = 25^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>Reverse Diode</b>					
Inverse diode continuous forward current $T_C = 25^\circ\text{C}$	$I_S$	-	-	47	A
Inverse diode direct current, pulsed $T_C = 25^\circ\text{C}$	$I_{SM}$	-	-	188	
Inverse diode forward voltage $V_{GS} = 0\text{ V}, I_F = 94\text{ A}$	$V_{SD}$	-	1.1	1.7	V
Reverse recovery time $V_R = 30\text{ V}, I_F = I_S, di_F/dt = 100\text{ A}/\mu\text{s}$	$t_{rr}$	-	75	115	ns
Reverse recovery charge $V_R = 30\text{ V}, I_F = I_S, di_F/dt = 100\text{ A}/\mu\text{s}$	$Q_{rr}$	-	0.15	0.25	$\mu\text{C}$



### Power dissipation


$$P_{\text{tot}} = f(T_C)$$



### Drain current

$$I_D = f(T_C)$$


parameter:  $V_{GS} \geq 4 \text{ V}$



### Safe operating area

$$I_D = f(V_{DS})$$


parameter:  $D = 0, T_C = 25^\circ\text{C}$



### Transient thermal impedance

$$Z_{\text{th JC}} = f(t_p)$$


parameter:  $D = t_p / T$



### Typ. output characteristics

$$I_D = f(V_{DS})$$


parameter:  $t_p = 80 \mu s$ ,  $T_j = 25^\circ C$



### Typ. drain-source on-resistance

$$R_{DS(on)} = f(I_D)$$


parameter:  $t_p = 80 \mu s$ ,  $T_j = 25^\circ C$



### Typ. transfer characteristics $I_D = f(V_{GS})$

parameter:  $t_p = 80 \mu s$


$$V_{DS} \geq 2 \times I_D \times R_{DS(on)max}$$



### Drain-source on-resistance

$$R_{DS(on)} = f(T_j)$$


parameter:  $I_D = 33\text{ A}$ ,  $V_{GS} = 4.5\text{ V}$



### Gate threshold voltage

$$V_{GS(th)} = f(T_j)$$


parameter:  $V_{GS} = V_{DS}$ ,  $I_D = 90\mu\text{A}$



### Typ. capacitances

$$C = f(V_{DS})$$


parameter:  $V_{GS} = 0\text{ V}$ ,  $f = 1\text{ MHz}$



### Forward characteristics of reverse diode



$$I_F = f(V_{SD})$$

parameter:  $T_j$ ,  $t_p = 80\mu\text{ s}$



**Avalanche energy**  $E_{AS} = f(T_j)$   
 parameter:  $I_D = 47 \text{ A}$ ,  $V_{DD} = 25 \text{ V}$   
 $R_{GS} = 25 \Omega$ ,  $L = 222 \mu\text{H}$

**Typ. gate charge**  
 $V_{GS} = f(Q_{\text{Gate}})$   
 parameter:  $I_{D \text{ puls}} = 47 \text{ A}$



**Drain-source breakdown voltage**  
 $V_{(BR)DSS} = f(T_j)$

