

SD210 / SD212 / SD214

FEATURES

- High Input to Output Isolation 120dB
- Low On Resistance 30 Ohm
- Low Feedthrough and Feedback Transients
- Low Capacitance:
 - Input (Gate) 2.4pF typ.
 - Output 1.3pF typ.
 - Feedback 0.3pF typ.
- No protection Diode from Gate to Substrate for Very High Impedance Applications
- Maximum Gate Voltage $\pm 40V$

APPLICATIONS

SD210:

- Analog Switch Driver

SD212 and SD214:

- Analog Switches
- High-Speed Digital Switches
- Multiplexers
- A to D Converters
- D to A Converters
- Choppers
- Sample & Hold



DESCRIPTION

The Calogic SD210 is a 30V analog switch driver without a built-in protection diode from gate to substrate for use with SD212 and SD214 DMOS analog switches.

ORDERING INFORMATION

| Part | Package | Temperature Range |
|---------|--------------------------|-------------------|
| SD210E | Hermetic TO-72 Package | -55°C to +125°C |
| XSS210 | Sorted Chips in Carriers | -55°C to +125°C |
| SD212DE | Hermetic TO-72 Package | -55°C to +125°C |
| XSD212 | Sorted Chips in Carriers | -55°C to +125°C |
| SD214DE | Hermetic TO-72 Package | -55°C to +125°C |
| XSD214 | Sorted Chips in Carriers | -55°C to +125°C |

SCHEMATIC DIAGRAM (Top View)



1Q-23

CD1-2

SD210 / SD212 / SD214



ABSOLUTE MAXIMUM RATINGS

Drain Current 50mA
 Total Device Dissipation at 25°C Case Temperature . . . 1.2W
 Storage Temperature Range -65°C to +200°C
 Lead Temperature (1/16" from case for 10 sec.) 300°C
 Operating Temperature Range -55°C to +125°C

| | PARAMETER | SD210 | SD212 | SD214 | UNIT |
|-----------------|-----------------|-------|-------|-------|-----------------|
| V _{DS} | Drain-to-Source | +30 | +10 | +20 | V _{dc} |
| V _{SD} | Source-to-Drain | +10 | +10 | +20 | V _{dc} |
| V _{DB} | Drain-to-Body | +30 | +15 | +25 | V _{dc} |
| V _{SB} | Source-to-Body | +15 | +15 | +25 | V _{dc} |
| V _{GS} | Gate-to-Source | ±40 | ±40 | ±40 | V _{dc} |
| V _{GB} | Gate-to-Body | ±40 | ±40 | ±40 | V _{dc} |
| V _{GD} | Gate-to-Drain | ±40 | ±40 | ±40 | V _{dc} |

DC CHARACTERISTICS (T_A = 25°C, unless otherwise specified)

| SYMBOL | PARAMETER | SD210 | | | SD212 | | | SD214 | | | UNITS | TEST CONDITIONS |
|--------------------------|----------------------------|-------|-----|-----|-------|-----|-----|-------|-----|-----|-------|---|
| | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | | |
| BREAKDOWN VOLTAGE | | | | | | | | | | | | |
| BV _{DS} | Drain-to-Source | 30 | 35 | | | | | | | | V | V _{GS} = V _{BS} = 0V, I _D = 10μA |
| | | 10 | 25 | | 10 | 25 | | 20 | 25 | | | V _{GS} = V _{BS} = -5V, I _S = 10nA |
| BV _{SD} | Source-to-Drain | 10 | | | 10 | | | 20 | | | | V _{GD} = V _{BD} = -5V, I _D = 10nA |
| BV _{DB} | Drain-to-Body | 15 | | | 15 | | | 25 | | | | V _{GB} = 0V, source OPEN, I _D = 10nA |
| BV _{SB} | Source-to-Body | 15 | | | 15 | | | 25 | | | | V _{GB} = 0V, drain OPEN, I _S = 10μA |
| LEAKAGE CURRENT | | | | | | | | | | | | |
| I _{DS} (OFF) | Drain-to-Source | | 1 | 10 | | 1 | 10 | | | | nA | V _{GS} = V _{BS} = -5V, V _{DS} = +10V |
| | | | | | | | | | 1 | 10 | | V _{GS} = V _{BS} = -5V, V _{DS} = +20V |
| I _{SD} (OFF) | Source-to-Drain | | 1 | 10 | | 1 | 10 | | | | | V _{GS} = V _{BD} = -5V, V _{SD} = +10V |
| | | | | | | | | | 1 | 10 | | V _{GS} = V _{BD} = -5V, V _{SD} = +20V |
| I _{GBS} | Gate | | | 0.1 | | | 0.1 | | | 0.1 | | V _{DB} = V _{SB} = 0V, V _{GS} = ±40V |
| V _T | Threshold Voltage | 0.5 | 1.0 | 2.0 | 0.1 | 1.0 | 2.0 | 0.1 | 1.0 | 2.0 | V | V _{DS} = V _{GS} = V _T , I _S = 1μA, V _{SB} = 0V |
| r _{DS} (ON) | Drain-to-Source Resistance | | 50 | 70 | | 50 | 70 | | 50 | 70 | Ω | I _D = 1.0mA, V _{SB} = 0, V _{GS} = +5V |
| | | | 30 | 45 | | 30 | 45 | | 30 | 45 | | I _D = 1.0mA, V _{SB} = 0, V _{GS} = +10V |
| | | | 23 | | | 23 | | | 23 | | | I _D = 1.0mA, V _{SB} = 0, V _{GS} = +15V |
| | | | 19 | | | 19 | | | 19 | | | I _D = 1.0mA, V _{SB} = 0, V _{GS} = +20V |
| | | | 17 | | | 17 | | | 17 | | | I _D = 1.0mA, V _{SB} = 0, V _{GS} = +25V |

AC ELECTRICAL CHARACTERISTICS

| SYMBOL | PARAMETER | SD210 | | | SD212 | | | SD214 | | | UNITS | TEST CONDITIONS |
|----------------------------------|--------------------------|-------|-----|-----|-------|-----|-----|-------|-----|-----|-------|--|
| | | MIN | TYP | MAX | MIN | TYP | MAX | MIN | TYP | MAX | | |
| g _{fs} | Forward Transconductance | 10 | 15 | | 10 | 15 | | 10 | 15 | | ms | V _{DS} = 10V, V _{SB} = 0V, I _D = 20mA, f = 1kHz |
| SMALL SIGNAL CAPACITANCES | | | | | | | | | | | | |
| C _(GS+GD+GB) | Gate Node | | 2.4 | 3.5 | | 2.4 | 3.5 | | 2.4 | 3.5 | pF | V _{DS} = 10V, f = 1MHz V _{GS} = V _{BS} = -15V |
| C _(GD+DB) | Drain Node | | 1.3 | 1.5 | | 1.3 | 1.5 | | 1.3 | 1.5 | | |
| C _(GS+SB) | Source Node | | 3.5 | 5.5 | | 3.5 | 5.5 | | 3.5 | 5.5 | | |
| C _{DG} | Reverse Transfer | | 0.3 | 0.5 | | 0.3 | 0.5 | | 0.3 | 0.5 | | |

Information furnished by Calogic is believed to be accurate and reliable. However, no responsibility is assumed for its use: nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent rights of Calogic.