

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The **ASI VHB40-28S** is Designed for

FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	5.0 A
V_{CB0}	65 V
V_{CEO}	35 V
V_{EBO}	4.0 V
P_{DISS}	60 W
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	2.9 °C/W

PACKAGE STYLE .380 4L STUD

DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.220 / 5.59	.230 / 5.84
B	.980 / 24.89	
C	.370 / 9.40	.385 / 9.78
D	.004 / 0.10	.007 / 0.18
E	.320 / 8.13	.330 / 8.38
F	.100 / 2.54	.130 / 3.30
G	.450 / 11.43	.490 / 12.45
H	.090 / 2.29	.100 / 2.54
I	.155 / 3.94	.175 / 4.45
J		.750 / 19.05

ORDER CODE: ASI10727

CHARACTERISTICS $T_c = 25\text{ }^\circ\text{C}$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	I _C = 200 mA	35			V
BV_{CES}	I _C = 200 mA	65			V
BV_{CBO}	I _C = 10 mA	65			V
BV_{EBO}	I _E = 10 mA	4.0			V
I_{CES}	V _{CE} = 30 V			10	mA
I_{CBO}	V _{CB} = 30 V			1.0	mA
h_{FE}	V _{CE} = 5.0 V I _C = 500 mA	5.0		200	---
C_{ob}	V _{CB} = 30 V f = 1.0 MHz			65	pF
P_G	V _{CE} = 28 V P _{IN} = 7.0 W f = 175 MHz	7.6			dB
η_C		60			%