

Tyco/Electronics
 Raychem Circuit Protection
 308 Constitution Drive
 Menlo Park, CA 94025-1164
 Phone: 800-227-4856
 Fax: 800-227-4866

PolySwitch® Power Switch Devices

PRODUCT: RYC8220-2M
 DOCUMENT: SCD24596
 PCN: 563577-000
 REV LETTER: C
 REV DATE: AUGUST 2, 2001
 PAGE NO.: 1 OF 2

Specification Status: Released

ABSOLUTE MAXIMUM RATINGS (Note 1)

Parameter	Symbol	Value	Units
Max supply voltage	V _{IN}	+8	V
Fault flag voltage	V _{FLG}	+8	V
Fault flag current	I _{FLG}	50	μA
Output voltage	V _{OUT}	+8	V
Output current	I _{OUT}	Internally limited	A
Control input	V _{EN}	- 0.3 to +12.0	V
Storage temperature	T _S	- 65 to +150	°C
Max lead temperature during soldering (5 sec.)		260	°C

OPERATING RATINGS (Note 3)

Parameter	Symbol	Value	Units
Supply voltage	V _{IN}	+3 to +5.5	V
Continuous output current (each output)	I _{OUT}	0.6	A
Ambient operating temperature	T _A	-40 to +85	°C
Thermal resistance (SO-8)	θ _{JA}	120	°C/W

ELECTRICAL CHARACTERISTICS (V_{IN} = +5V; T_A = 25°C; unless noted.)

Power switch	Condition	Min	Typ	Max	Units
Switch Resistance	V _{IN} = 5V, I _{OUT} = 500mA, each switch		95	120	mΩ
	V _{IN} = 3.3V, I _{OUT} = 500mA, each switch		90	110	mΩ
Output Turn-On Time	R _L = 10Ω each output, consists of delay+rise time		3.6	12	ms
Output Turn-Off Time	R _L = 10Ω each output, consists of delay+fall time		2	40	μs

Current limit	Condition	Min	Typ	Max	Units
Short-Circuit Current Limit	Each output (enable into 0Ω load)	0.6	0.9	1.25	A
	Each output (3Ω load hot-plugged into EN device), V _{OUT} = 4.0V	0.6	0.9	1.25	A

Enable input	Condition	Min	Typ	Max	Units
Enable Input Threshold	Low-to-high transition		1.5	2.4	V
	High-to-low transition, Note 4	0.8	1.5		V
Enable Input Current	V _{EN} = 0V to 5.5V		0.01	1	μA
Enable Input Capacitance				5	pF

Supply current	Condition	Min	Typ	Max	Units
Supply Current	Switch off, OUT = open; Note 4		0.5	5	μA
	Switches on, OUT = open; Note 4		200	250	μA
Output Leakage Current	Each output (output disabled)			10	μA

OT, UVLO/OVLO	Condition	Min	Typ	Max	Units
Overtemperature Shutdown Threshold	T _J increasing		135		C
	T _J decreasing		125		C
UVLO Threshold	V _{IN} = increasing		2.5		V
	V _{IN} = decreasing		2.3		V
OVLO Threshold	V _{IN} = increasing		6.4		V
	V _{IN} = decreasing		6.1		V

Error flag	Condition	Min	Typ	Max	Units
Error Flag Output Resistance	V _{IN} = 5V, I _L = 10μA, Note 5		50	100	Ω
	V _{IN} = 3.3V, I _L = 10μA, Note 5		80	100	Ω
Error flag output delay	Fault on overcurrent, Note 6	6	9	15	ms
Error Flag Off Current	V _{FLAG} = 5V		0.01	1	μA

Tyco/Electronics
Raychem Circuit Protection
 308 Constitution Drive
 Menlo Park, CA 94025-1164
 Phone: 800-227-4856
 Fax: 800-227-4866


PolySwitch® Power Switch Devices

PRODUCT: RYC8220-2M
 DOCUMENT: SCD24596
 PCN: 563577-000
 REV LETTER: C
 REV DATE: AUGUST 2, 2001
 PAGE NO.: 2 OF 2


ELECTRICAL CHARACTERISTICS - NOTES

- Note 1.** Exceeding the absolute maximum rating may damage the device.
Note 2. Devices are ESD sensitive. Handling precautions recommended.
Note 3. The device is not designed to function outside its operating rating.
Note 4. Off is $\leq 0.8V$ and on is $\geq 2.4V$ for the RYC8220-1 and RYC8220-3. Off is $\geq 2.4V$ and on is $\leq 0.8V$ for the RYC8220-2 and RYC8220-4. The enable input has approximately 200mV of hysteresis. Pull-down/Pull-up resistors are on chip for "-1" and "-2" configurations.
Note 5. Pull-up resistors are on chip.
Note 6. No error flag out delay on UVLO, OVLO and thermal shutdown.

PIN CONFIGURATION:




DEVICE MARKING:



PIN DESCRIPTIONS:

Pin Number	Pin Name	Pin Function
1, 4	EN	Enable (Input): Logic-compatible enables input. High input > 2.4V. Low input < 0.8V (-1, -3 active high, -2, -4 active low). Do not float.
2, 3	FLG	Fault Flag (Output): Active-low open-drain output. Indicates overcurrent, UVLO, OVLO and thermal shutdown.
6	GND	Ground: Supply return
7	IN	Supply Input: Output MOSFET drain. Also supplies IC's internal circuitry. Connect to positive supply.
5 and 8	OUT	Switch Output: Output MOSFET source. Typically connect to switched side of load.

MECHANICAL DIMENSIONS:



DIMENSION	MIN	MAX	MIN	MAX
	mm	mm	inch	inch
A	4.80	5.00	0.190	0.197
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.013	0.020
F	0.40	1.27	0.016	0.050
G	1.27 BSC		0.050 BSC	
J	0.18	0.25	0.0075	0.010
K	0.10	0.25	0.004	0.010
M	0°	8°	0°	8°
P	5.80	6.20	0.228	0.244