

Si photodiode S10170

RGB color sensor integrated in small and thin package



S10170 is a color sensor molded into a plastic package having a 3-channel (RGB) photodiode sensitive to the Red ($\lambda=590$ nm Min.), Green ($\lambda=480$ to 600 nm) and Blue ($\lambda=400$ to 540 nm) regions of the spectrum. When compared to the previous model (S9702), S10170 is significantly miniaturized the package size by 80 % in cubic volume and PC board mount space by 77 % in area. S10170 is ideal for RGB-LCD backlight monitors installed in such as mobile phones.

Features

- 3-channel (R, G, B) Si photodiode
- Small, thin package: 3.0 × 1.6 × 1.0 mm
- Active area: 1 × 1 mm/3-segment (RGB)
- RoHS-compatible
- Surface mount type

Applications

- Portable or mobile equipment
- RGB-LCD backlight monitors
- Detectors for various light sources
- Color detection


Absolute maximum ratings

Parameter	Symbol	Value	Unit
Reverse voltage	V_R Max	10	V
Operating temperature	T_{opr}	-25 to +85	°C
Storage temperature	T_{stg}	-40 to +100	°C


Electrical and optical characteristics ($T_a=25$ °C, per element)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ	Blue	-	400 to 540 800 to 1000	-	nm
		Green	-	480 to 600 760 to 1000	-	
		Red	-	590 to 1000	-	
Photo sensitivity	S	Blue ($\lambda=460$ nm)	0.16	0.21	-	A/W
		Green ($\lambda=540$ nm)	0.23	0.28	-	
		Red ($\lambda=640$ nm)	0.40	0.45	-	
Dark current	I_D	$V_R=1$ V, All elements	-	1	50	pA
Temperature coefficient of I_D	T_{CID}		-	1.12	-	times/°C
Rise time	t_r	$V_R=0$ V, $R_L=1$ k Ω , 10 to 90 %	-	0.1	-	μ s
Terminal capacitance	C_t	$V_R=0$ V, $f=10$ kHz	-	12	25	pF


Spectral response



Dark current vs. reverse voltage




Terminal capacitance vs. reverse voltage



Since this photodiode has sensitivity in the infrared region, infrared light must be filtered out as needed.

■ Dimensional outline (unit: mm)




KSPDA0174EA

■ Line-up of RGB color sensors

Type No.	Spectral response range		Peak sensitivity wavelength (nm)	Photo sensitivity $\lambda = \lambda_p$ (A/W)		Dark current $V_R = 1$ V all elements Max. (pA)	Active area (mm)		Package
	B	G		B	G		B	G	
S7505-01	B	400 to 540	460	B	0.18	200	B	1.5 × 1.5 (× 2)	Surface-mount type plastic
	G	480 to 600	540	G	0.23		G	1.5 × 1.5	
	R	590 to 720	620	R	0.16		R	1.5 × 1.5	
S9032-02	B	400 to 540	460	B	0.18	100	φ2/3-element		Surface-mount type plastic
	G	480 to 600	540	G	0.23				
	R	590 to 720	620	R	0.16				
S9702	B	400 to 540	460	B	0.18	50	1 × 1/3-element		Surface-mount type, miniature plastic
	G	480 to 600	540	G	0.23				
	R	590 to 720	620	R	0.16				
S8751	B	400 to 540	460	B	0.21	100	1 × 1		Surface-mount type plastic
	G	480 to 600	540	G	0.25				
	R	590 to 720	660	R	0.42				
S8752	B	400 to 540	460	B	0.21	100	1 × 1		Plastic
	R	590 to 720	660	R	0.42				

■ Application example

Optical feedback of backlight for TFT-LCD using a color sensor module C9303-04 (integrated with S9032-02)



LED: Made by Lumileds (LUXEON), <http://www.lumileds.com/>

KACCC0289EA

HAMAMATSU Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2007 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, www.hamamatsu.com

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Twin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741