


3MM (ROUND TYPE)(GAP) LED LAMP

3MM (Round Type) (Gap)
LED Lamp

Test Condition

Vr = 5V
If = 20mA
If = 10mA (MCD)




Dimensions in mm

Maximum Ratings (T_a = 25 °C)

	Symbol	Value	Unit
Reverse Voltage	V _R	5	Volts
Reverse Current		10	μA (Vr = 5V)
Operating Temperature	T _{amb}	-40 to 85	°C
Storage Temperature	T _S	-40 to 100	°C

Electrical and Electronic Characteristic

Part No.	Colour	Wave Length λ P(nm)	Δλ (nm)	Pd (mv)	If (mA)	Peak If (mA)	Vf (V)			Rec If (mA)	Iv (mad)	
							Min.	Typ.	Max.		Min.	Typ.
ST4002DR	Red Diffused	697	90	45	15	50	1.7	2.1	2.8	5-10	0.5	1.0
ST4002DG	Green Diffused	565	30	100	30	160	1.7	2.1	2.8	10-20	0.7	3.5
ST4002DY	Yellow Diffused	585	35	100	20	160	1.7	2.0	2.8	10-20	0.5	2.5



SEMTECH ELECTRONICS LTD.
(wholly owned subsidiary of HONEY TECHNOLOGY LTD.)

