


X00075

TR0007

ACTIVE

STX 6904 / ~~6905~~ CHIP**HIGH VOLTAGE PNP TRANSISTOR
MULTIPLE DIFFUSED EPITAXIAL**

Contact Area: .012 x .020

CONTACT METALLIZATION

Base/Emitter: > 30,000 Å Aluminum

Collector: > 2,000 Å Evaporated Gold

ASSEMBLY RECOMMENDATIONS

1. Eutectic Die Attach.
2. Ultrasonically Attach 5 MIL Aluminum Wire To Base/Emitter Contacts.

PARAMETER	TEST CONDITIONS *	TYPE	MIN.	MAX.	UNIT
BV _{CEO}	IC=1mA	STX 6904 NOUG	350		Vdc
BV _{CBO}	IC=100uA	STX 6905	400		Vdc
BV _{CER}	IC=100uA, RBE=1KOhms	STX 6904	400		Vdc
BV _{EBO}	IE=20uA	STX 6905	500		Vdc
I _{EBO}	VEB=4V	STX 6904	400		Vdc
I _{CBQ}	VCB=300V	STX 6905	500		Vdc
h _{FE}	VCE=15V, IC=100mA	ALL	6.0		Vdc
h _{FE}	VEB=4V	ALL		250	n Adc
h _{FE}	VCB=300V	STX 6904		500	n Adc
h _{FE}	VCB=400V	STX 6905		500	n Adc
h _{FE}	VCE=10V, IC=25mA		20	200	
h _{FE}	VCE=10V, IC=1mA		40	250	
V _{BE(SAT)}	VCE=10V, IC=1mA		20	200	
V _{CE(SAT)}	IC=25mA, VCE=10V			1.0	Vdc
C _{OB}	IC=25mA, IB=2.5mA			3.0	Vdc
h _{fe}	VCB=15V, f=2MHZ			20	pf
h _{fe}	VCE=20V, IC=10mA, f=5MHZ		4		

* Electrical characteristics measured at lot acceptance testing in a TO-5 package. Specifications subject to change without notice.

SSDI SOLID STATE DEVICES, INC.

P.O. Box 577, La Mirada, California, 90637-0577 TWX 910-583-4807
14830 Valley View Avenue, La Mirada, California, 90638 (213) 921-9660