TOSHIBA Photocoupler GaAlAs IRED + Photo IC

# TLP705F

Plasma Display Panel
Industrial Inverter
IGBT/Power MOSFET Gate Drive

TLP705F consists of a GaAlAs light emitting diode and a integrated photodetector.

This unit is 6-lead SDIP package. TLP705F is 50% smaller than 8PIN DIP and has suited the safety standard reinforced insulation class.

So mounting area in safety standard required equipment can be reduced. TLP705F is suitable for gate driving circuit of IGBT or power MOS FET. Especially TLP705F is capable of "direct" gate drive of lower Power IGBTs. Absolute Maximum ratings and electrical characteristics are the same as The TLP705 technical data sheets.

Peak output current : ±0.45 A (max)
 Operating frequency : 250kHz (max)
 Guaranteed performance over temperature : -40 to 100°C
 Supply current : 3mA (max)
 Power supply voltage : 10 to 20 V

Threshold input current : I<sub>FLH</sub> = 8 mA (max)
 Switching time (t<sub>pLH</sub> / t<sub>pHL</sub>) : 200 ns (max)
 Common mode transient immunity : ±10 kV/µs(min)

Isolation voltage : 5000 Vrms(min)
 UL Recognized :UL1577, File No.E67349

Construction Mechanical Rating

Creepage Distance	8.0 mm (min)
Clearance	8.0 mm (min)
Insulation Thickness	0.4 mm (min)

Option (D4)

TÜV approved : EN60747-5-2


Certificate No. R50033433

Maximum operating insulation voltage : 1140 Vpk Highest permissible over voltage : 8000 Vpk

# Unit in mm 4.58±0.25 6 5 4 9 7.62±0.25 7.62±0.25 1.27±0.2 0.75±0.25 11.5J101 TOSHIBA 11-5J101

Weight: 0.26 g (typ.)


# Pin Configuration (top view)



### **Truth Table**

Input	LED	Tr1	Tr2	Output
Н	ON	ON	OFF	Н
L	OFF	OFF	ON	L

### **Schematic**



A 0.1  $\mu$ F bypass capacitor must be connected between pin 6 and 4. (See Note 6)

## RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in his document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No
  responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which
  may result from its use. No license is granted by implication or otherwise under any patents or other rights of
  TOSHIBA or the third parties.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.
- Please contact your sales representative for product-by-product details in this document regarding RoHS
  compatibility. Please use these products in this document in compliance with all applicable laws and regulations
  that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses
  occurring as a result of noncompliance with applicable laws and regulations.