TOSHIBA


Toshiba TLxE183 Series LEDs

Features

5mm Package
InGaAIP Technology
All Plastic Mold Type
Water Clear Lens
Fast Response Time, Capable of Pulse Operation
High Power Luminous Intensity

Applications

Suitable for Outdoor Message Signboard, Safety equipment, etc.



Series Line-Up

Part Number	Color	Material		
TLGE183P	Ultra Bright Yellow Green	InGaAIP		
TLPGE183P	Ultra Pure Green	InGaAIP		

Maximum Ratings (Ta=25°C)

Part Number	Forward Current IF	Reverse Voltage V _R	Power Dissipation PD	Operating Temperature Topr	Storage Temperature Tstg
TLGE183P	50	4	140.00	−30 ~ 85	−40 ~ 120
TLPGE183P	50	4	140.00	−30 ~ 85	−40 ~ 120
Unit	mA	V	mW	°C	°C

Company Headquarters 3 Norhway Lane North Latham, New York 12110 Toll Free: 800.984.5337 Fax: 518.785.4725



Toll Free: 800.984.5337 Fax: 714.850.9314



Toshiba TLxE183 Series LEDs

Electrical and Optical Characteristics (Ta=25°C)

Part Number	PWL nm λP	Material	View Angle	Luminous Intensity			Forward Voltage V _F				Rev Current IR		
			2θ1/2	min.	typ.	max.	IF@	min.	typ.	max.	IF@	max.	VR@
TLGE183P	574	InGaAIP	7°	1530.00	5000.00	_	20mA	-	2.27	2.80	20mA	50	4V
TLPGE183P	562	InGaAIP	7°	476.00	2000.00	_	20mA	-	2.27	2.80	20mA	50	4V
-	nm	-	deg		mcd		-		٧		-	μ A	-

Precautions

- Soldering temperature: 260°C max, soldering time: 3 s max (soldering portion of lead: up to 2 mm from the body of the device).
- If the lead is formed, the lead should be formed up to 5 mm from the body of the device without forming stress to the resin. Soldering should be performed after lead forming.
- be performed after lead forming.

 This visible LED lamp also emits some IR light. If a photodetector is located near the LED lamp, please ensure that it will not be affected by this IR light.

NOTICE:

- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
- In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc..
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- Gallium arsenide (GaAs) is a substance used in the products described in this document. GaAs dust and fumes are toxic. Do not break, cut or pulverize the product, or use chemicals to dissolve them. When disposing of the products, follow the appropriate regulations. Do not dispose of the products with other industrial waste or with domestic garbage.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.



Fax: 518.785.4725

Web: www.marktechopto.com | Email: info@marktechopto.com


West Coast Sales Office 950 South Coast Drive. Suite 265

Costa Mesa, California 92626 Toll Free: 800.984.5337 Fax: 714.850.9314

TOSHIBA

Toshiba TLxE183 Series LEDs

TLGE183P Graphs




Company Headquarters 3 Norhway Lane North Latham, New York 12110 Toll Free: 800.984.5337 Fax: 518.785.4725



West Coast Sales Office 950 South Coast Drive, Suite 265 Costa Mesa, California 92626 Toll Free: 800.984.5337 Fax: 714.850.9314

Web: www.marktechopto.com | Email: info@marktechopto.com

TLPGE183P Graphs



Company Headquarters 3 Norhway Lane North Latham, New York 12110 Toll Free: 800.984.5337 Fax: 518.785.4725



West Coast Sales Office 950 South Coast Drive, Suite 265 Costa Mesa, California 92626 Toll Free: 800.984.5337 Fax: 714.850.9314