

Super LLD (For PFC circuit) (current continuous mode)

LOW LOSS SUPER HIGH SPEED RECTIFIER


■ Features

- Super high speed switching
- High reliability by planer design


■ Applications

- PFC circuit (current continuous mode)

■ Outline drawings, mm



■ Connection diagram



■ Maximum ratings and characteristics

● Maximum ratings

Item	Symbol	Conditions	Rating	Unit
Repetitive peak reverse voltage	V_{RRM}		600	V
Non-Repetitive peak reverse voltage	V_{RSM}		600	V
Peak forward current	I_P		30*	A
Average output current	I_o	Square wave duty=1/2, $T_c=97^\circ C$	10*	A
Non-Repetitive surge current	I_{FSM}	Sine wave 10ms, 1shot	40	A
Operating junction temperature	T_j		150	$^\circ C$
Storage temperature	T_{stg}		-40 to +150	$^\circ C$

* Out put current of centertap full wave connection.

● Electrical characteristics (Ta=25°C Unless otherwise specified)







Item	Symbol	Conditions	Characteristics	Unit
Reverse recovery peak current **	I_{RP}	$I_F=5A, -di/dt=200A/\mu s, V_R=380V, T_j=100^\circ C$	Typ. 2.5	A
Reverse recovery time **	t_{rr}	$I_F=0.1A, I_R=0.2A, I_{rec}=0.05A$	Max. 30.0	ns
Forward voltage **	V_F	$I_F=15A$	Max. 5.0	V
Reverse current **	I_R	$V_R=V_{RRM}$	Max. 50.0	μA
Thermal resistance	$R_{th(j-c)}$	Junction to case	Max. 2.0	$^\circ C/W$

** Rating per element

● Mechanical characteristics

Mounting torque	Recommended torque	0.4 to 0.6	N·m
Approximate mass		2.0	g

■ Characteristics



λ :Conduction angle of forward current for each rectifier element
Io:Output current of center-tap full wave connection

