


Material:

- Waterproof Rate: IP67
- LED Holder: Brass, Nickel plating
- LED: $\varnothing 5$ MM, Red
- Lense Color: Water Clear
- Forward Voltage: Red Typ. 2.2V/Max.2.4V
- Forward Current: Red Max. 30mA
- Luminous Intensity: Red Typ.5,000(Mcd)
- Reverse Voltage: 5V DC
- Gasket: EPDM, Black
- Screw Nut: Brass, Nickel plating
- Operating Temperature: $-40^{\circ}\text{C} \sim +80^{\circ}\text{C}$
- For Panel Thickness 6.5MM Max.



Recommended Panel Cut-Out

QC Quality Control: Important Dimension to check
Unit: MM ± 0.25 MM

Ⓜ = Assmann logo



ITEM NO.

A-LED8-1RBAS-MR7-1-R

TITLE

Waterproof LED - Red color, M8 size connector, $\varnothing 5$ MM, Metal housing, Solder pins, IP67 unmated

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2010 by Assmann Electronic Components
All International Rights Reserved