

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:


The **ASI SD1134** is Designed for Class C UHF Communications

FEATURES:

- $P_G = 10$ dB Typical at 470 MHz
- **Omnigold™** Metallization System

MAXIMUM RATINGS

I_C	0.75 A
V_{CB}	36 V
P_{DISS}	5.0 W @ $T_C = 25$ °C
T_J	-65 °C to +200 °C
T_{STG}	-65 °C to +150 °C
θ_{JC}	35 °C/W

PACKAGE STYLE .280 4L STUD


DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	1.010 / 25.65	1.055 / 26.80
B	.220 / 5.59	.230 / 5.84
C	.270 / 6.86	.285 / 7.24
D	.003 / 0.08	.007 / 0.18
E	.117 / 2.97	.137 / 3.48
F	.572 / 14.53	
G	.130 / 3.30	
H	.245 / 6.22	.255 / 6.48
I	.640 / 16.26	
J	.175 / 4.45	.217 / 5.51
K	.275 / 6.99	.285 / 7.24

CHARACTERISTICS $T_C = 25$ °C

SYMBOL	TEST CONDITIONS			MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CEO}	$I_C = 25$ mA			16			V
BV_{CES}	$I_C = 5.0$ mA			36			V
BV_{EBO}	$I_E = 1.0$ mA			4.0			V
I_{CBO}	$V_{CB} = 15$ V					1.0	mA
h_{FE}	$V_{CE} = 5.0$ V	$I_C = 100$ mA		20			---
C_{OB}	$V_{CB} = 12$ V	$f = 1.0$ MHz			6.0		pF
P_{OUT} P_G	$V_{CE} = 12.0$ V	$P_{IN} = 0.2$ W	$f = 470$ MHz	2.0 10			W dB