



WP12

12 Watt Single Output Regulated Power Supplies





Features:
 N.A. AC input
 Fully enclosed plastic case
 Fully regulated output
 High Efficiency
 Warranty: 5 years

Environmental
 Operating temperature.....0° C to 40° C
 Storage temperature.....-55° C to 85° C
 Weight: 0.5 lbs

EMI
 Meets FCC class B

Safety
 UL 1950
 cUL Listed to CSA 22.2 No. 950

Electrical specifications


Input
 Voltage.....90-132VAC
 Current.....0.75A
 Frequency.....47-63 Hz
 Input connector.....2 Pin NEMA 5/15 plug

Output
 Line regulation.....TYP 1%
 Load regulation.....5% Max
 Set point.....5% of rated output
 Hold up time.....12 ms min. at full load 115 V

Over voltage protection.....Built-in
 Over current protection.....Built-in
 Short circuit protection.....Pulsing Mode, auto recovery
 Ripple/noise(Vp-p).....1%
 Output connector.....barrel type(5.5 x 2.5 x 9.5mm)

Output Electrical Specifications

Model No.	Voltage	Power	Current
WP1205-760	5	12	2.4A
WP1212-760	12	12	1A
WP1215-760	15	12	0.8A
WP1218-760	18	12	0.67A
WP1224-760	24	12	0.5A

Polarity: COM  +V

[Quality Power Supplies](#) |
 [Agency Certifications](#) |
 [Output Connectors](#) |
 [Custom Requests](#) |
 [About Us](#) |
 [Qu Management Team](#) |
 [Job Opportunites](#) |
 [Elpac News](#) |
 [Sales Representatives](#) |
 [Distributors](#) |
 [Catalog Reque](#)
[Power Supplies](#) |
 [External Power Supplies](#) |
 [Open Frame Power Supplies](#) |
 [Medical Power Supplies](#) |
 [Custor](#)