


YG801C09R

(90V / 5A TO-220F15)

SCHOTTKY BARRIER DIODE

Outline Drawings



Features

- Low V_F
- Super high speed switching.
- High reliability by planer design.

Applications

- High speed power switching.

Maximum Ratings and Characteristics

- Absolute Maximum Ratings

Item	Symbol	Conditions	Rating	Unit
Repetitive peak reverse voltage	V_{RRM}		90	V
Repetitive peak surge reverse voltage	V_{RSM}	$t_w=500ns$, $duty=1/40$	100	V
Isolation voltage	V_{iso}	Terminals to Case, AC, 1min.	1500	V
Average output current	I_o	$duty=1/2$, $T_c=117^\circ C$ Square wave	5*	A
Surge current	I_{FSM}	Sine wave 10ms	60	A
Operating junction temperature	T_j		+150	$^\circ C$
Storage temperature	T_{stg}		-40 to +150	$^\circ C$

* Out put current of centertap full wave connection.

- Electrical Characteristics ($T_a=25^\circ C$ Unless otherwise specified)


Item	Symbol	Conditions	Max.	Unit
Forward voltage drop **	V_F	$I_F=2.0A$	0.9	V
Reverse current **	I_R	$V_R=V_{RRM}$	2.0	mA
Thermal resistance	$R_{th(j-c)}$	Junction to case	5.0	$^\circ C/W$

** Rating per element







- Mechanical Characteristics



Mounting torque	Recommended torque	0.3 to 0.5	N · m
Weight		2.3	g

Connection Diagram



■ Characteristics





电子产品世界
EEPW.com.cn