

YG808C10R

(100V / 30A TO-220F15)

SCHOTTKY BARRIER DIODE

Features

- Low VF
- Super high speed switching.
- High reliability by planer design.

Applications

- High speed power switching.

Maximum Ratings and Characteristics

Absolute Maximum Ratings

Item	Symbol	Conditions	Rating	Unit
Repetitive peak reverse voltage	V_{RRM}		100	V
Repetitive peak surge reverse voltage	V_{RSM}	$t_w=500\text{ns}, \text{duty}=1/40$	100	V
Isolation voltage	V_{iso}	Terminals to Case, AC. 1min.	1500	V
Average output current	I_o	duty=1/2, $T_c=80^\circ\text{C}$ Square wave	30*	A
Surge current	I_{FSM}	Sine wave 10ms	180	A
Operating junction temperature	T_j		+150	$^\circ\text{C}$
Storage temperature	T_{stg}		-40 to +150	$^\circ\text{C}$

* Out put current of centertap full wave connection.

Electrical Characteristics ($T_a=25^\circ\text{C}$ Unless otherwise specified)

Item	Symbol	Conditions	Max.	Unit
Forward voltage drop **	V_F	$I_F=10\text{A}$	0.80	V
Reverse current **	I_R	$V_R=V_{RRM}$	20.0	mA
Thermal resistance	$R_{th(j-c)}$	Junction to case	2.0	$^\circ\text{C}/\text{W}$

** Rating per element

Mechanical Characteristics

Mounting torque	Recommended torque	0.3 to 0.5	$\text{N} \cdot \text{m}$
Weight		2.3	g

■ Characteristics



